



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**2300**  
 Component  
**Diesel Engine**  
 Fluid  
**SHELL ROTELLA T 15W40 (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0900499</b>	WC0871361	WC0828995
Sample Date		Client Info		<b>11 Mar 2024</b>	15 Jan 2024	07 Nov 2023
Machine Age	mls	Client Info		<b>190000</b>	171000	0
Oil Age	mls	Client Info		<b>20000</b>	20000	20000
Filter Age	mls	Client Info		<b>20000</b>	20000	20000
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>12</b>	14	12
Chromium	ppm	ASTM D5185m	>20	<b>1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	<1	0
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>6</b>	6	7
Lead	ppm	ASTM D5185m	>40	<b>1</b>	<1	2
Copper	ppm	ASTM D5185m	>330	<b>1</b>	<1	<1
Tin	ppm	ASTM D5185m	>15	<b>1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>8</b>	6	7
Potassium	ppm	ASTM D5185m	>20	<b>10</b>	10	11
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.5</b>	0.4	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.3</b>	9.5	9.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.2</b>	21.3	21.8
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>1</b>	4	3
Boron	ppm	ASTM D5185m	316	<b>43</b>	31	44
Barium	ppm	ASTM D5185m	0.0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	1.2	<b>59</b>	56	65
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	24	<b>472</b>	517	551
Calcium	ppm	ASTM D5185m	2292	<b>1551</b>	1558	1608
Phosphorus	ppm	ASTM D5185m	1064	<b>1025</b>	1038	967
Zinc	ppm	ASTM D5185m	1160	<b>1162</b>	1244	1149
Sulfur	ppm	ASTM D5185m	4996	<b>3130</b>	3070	2840
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>16.8</b>	17.2	17.9
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	<b>8.2</b>	7.5	7.6
Visc @ 100°C	cSt	ASTM D445	15.7	<b>13.4</b>	13.3	13.3



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0900499  
**Lab Number** : 06156762  
**Unique Number** : 10992185  
**Test Package** : FLEET

**Ergon Trucking Inc. - MAR605**  
 35020 State Route 7  
 Marietta, OH  
 US 45768-5236  
 Contact: JASON JULIAN

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: