

WEAR NORMAL CONTAMINATION NORMAL FLUID CONDITION NORMAL

Machine Id VOLVO A45G 13418 (S/N 752224) Component Brake Cooling System Fluid {not provided} (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

WEAR

All component wear rates are normal.

CONTAMINATION


There is no indication of any contamination in the fluid.


FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		ASC0006053		
Sample Date		Client Info		03 Apr 2024		
Machine Age	hrs	Client Info		750		
Oil Age	hrs	Client Info		750		
Filter Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Filter Changed		Client Info		N/A		
Sample Status				NORMAL		
Iron	ppm	ASTM D5185m	>50	34		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>10	4		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	00	0		
Aluminum	ppm	ASTM D5185m	>30	2		
Lead	ppm	ASTM D5185m	>50	<1		
Copper	ppm	ASTM D5185m	>200	26		
Tin	ppm	ASTM D5185m	>20	<1		
Vanadium	ppm	ASTM D5185m	NONE	0		
White Metal	scalar	*Visual *Visual	NONE	NONE		
Yellow Metal	scalar	^\/ICLI3I				
		visuai	NONL	NONE		
Silicon	ppm	ASTM D5185m	>50	13		
Silicon	ppm	ASTM D5185m	>50	13		
Silicon Potassium	ppm	ASTM D5185m ASTM D5185m	>50 >20	13 3		
Silicon Potassium Water	ppm ppm	ASTM D5185m ASTM D5185m WC Method	>50 >20 >0.2	13 3 NEG		
Silicon Potassium Water Silt	ppm ppm scalar	ASTM D5185m ASTM D5185m WC Method *Visual	>50 >20 >0.2 NONE	13 3 NEG NONE		
Silicon Potassium Water Silt Debris	ppm ppm scalar scalar	ASTM D5185m ASTM D5185m WC Method *Visual *Visual	>50 >20 >0.2 NONE NONE	13 3 NEG NONE NONE		
Silicon Potassium Water Silt Debris Sand/Dirt	ppm ppm scalar scalar scalar	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual	>50 >20 >0.2 NONE NONE NONE	13 3 NEG NONE NONE NONE		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance	ppm ppm scalar scalar scalar scalar	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual	>50 >20 >0.2 NONE NONE NONE NORML	13 3 NEG NONE NONE NONE NORML		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water	ppm ppm scalar scalar scalar scalar scalar scalar	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NONE NORML NORML NEG		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium	ppm ppm scalar scalar scalar scalar scalar scalar	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron	ppm ppm scalar scalar scalar scalar scalar scalar gppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium	ppm ppm scalar scalar scalar scalar scalar scalar ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium Molybdenum	ppm ppm scalar scalar scalar scalar scalar scalar ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0 <1		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium Molybdenum Manganese	ppm ppm scalar scalar scalar scalar scalar scalar ppm ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0 <1 <1		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium Molybdenum Manganese Magnesium	ppm ppm scalar scalar scalar scalar scalar ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0 <1 <1 <1 8		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium Malybdenum Manganese Magnesium	ppm ppm scalar scalar scalar scalar scalar ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0 <1 <1 <1 8 3364		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium Barium Molybdenum Manganese Magnesium Calcium	ppm ppm scalar scalar scalar scalar scalar ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0 <1 <1 8 3364 1421		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm scalar scalar scalar scalar scalar ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0 <1 <1 <1 8 3364 1421 1495		
Silicon Potassium Water Silt Debris Sand/Dirt Appearance Odor Emulsified Water Sodium Boron Barium Barium Molybdenum Manganese Magnesium Calcium	ppm ppm scalar scalar scalar scalar scalar ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m WC Method *Visual *Visual *Visual *Visual *Visual *Visual ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >20 >0.2 NONE NONE NONE NORML NORML	13 3 NEG NONE NONE NORML NORML NEG 2 118 0 <1 <1 8 3364 1421		

Submitted By: Service - Brandon Lewis





117 - ASCENDUM MACHINERY INC - GREENVILLE 2002 N GREENE ST GREENVILLE, NC US 27834 Contact: Brandon Lewis brandon.lewis@ascendummachinery.com T: F: (704)494-8197



: 25 Apr 2024 - Don Baldridge Unique Number : 10993524 Diagnosed Test Package : CONST Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

: 23 Apr 2024

: 24 Apr 2024

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received

Tested

Laboratory

Sample No.

Lab Number : 06158101

: ASC0006053