



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(C0810283) {UNASSIGNED}
Machine Id
834016
Component
Natural Gas Engine
Fluid
PETRO CANADA DURON SHP 15W40 (8 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0118026	GFL0109914	GFL0109870
Sample Date		Client Info		23 Apr 2024	29 Jan 2024	12 Jan 2024
Machine Age	hrs	Client Info		1212	1194	1098
Oil Age	hrs	Client Info		27	594	507
Filter Age	hrs	Client Info		27	594	507
Oil Changed		Client Info		Not Changed	Changed	Not Changed
Filter Changed		Client Info		Not Changed	Changed	Not Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	25	23	28
Chromium	ppm	ASTM D5185m	>4	0	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	0	2	2
Lead	ppm	ASTM D5185m	>30	0	4	3
Copper	ppm	ASTM D5185m	>35	<1	4	5
Tin	ppm	ASTM D5185m	>4	0	2	1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>+100	3	9	9
Potassium	ppm	ASTM D5185m	>20	<1	3	4
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	5.5	10.0	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.9	21.7	20.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<1	6	4
Boron	ppm	ASTM D5185m	0	12	0	0
Barium	ppm	ASTM D5185m	0	0	0	3
Molybdenum	ppm	ASTM D5185m	60	66	61	66
Manganese	ppm	ASTM D5185m	0	<1	2	2
Magnesium	ppm	ASTM D5185m	1010	991	865	956
Calcium	ppm	ASTM D5185m	1070	1226	1042	1139
Phosphorus	ppm	ASTM D5185m	1150	1121	848	882
Zinc	ppm	ASTM D5185m	1270	1394	1111	1174
Sulfur	ppm	ASTM D5185m	2060	3822	2479	3017
Oxidation	Abs/.1mm	*ASTM D7414	>25	12.8	16.1	15.4
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.7	2.9	3.4
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	13.1	13.2


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0118026
Lab Number : 06158743
Unique Number : 10994166
Test Package : FLEET

Received : 24 Apr 2024
Tested : 25 Apr 2024
Diagnosed : 25 Apr 2024 - Wes Davis

GFL Environmental - 010 - Stockbridge
 1280 Rum Creek Parkway
 Stockbridge, GA
 US 30281
 Contact: JOSHUA TINKER
 joshuatinker@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: