



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**(FAN294)**  
Machine Id  
**424075**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0111522</b>	GFL0111513	GFL0111549
Sample Date		Client Info		<b>18 Apr 2024</b>	10 Apr 2024	25 Mar 2024
Machine Age	hrs	Client Info		<b>0</b>	0	0
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	N/A	Not Changd
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>165	<b>45</b>	50	45
Chromium	ppm	ASTM D5185m	>5	<b>2</b>	2	2
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>4</b>	2	4
Lead	ppm	ASTM D5185m	>150	<b>4</b>	4	4
Copper	ppm	ASTM D5185m	>90	<b>57</b>	69	56
Tin	ppm	ASTM D5185m	>5	<b>1</b>	1	1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>35	<b>15</b>	16	14
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	0	<1
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	<b>1.3</b>	1.6	1.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>12.7</b>	12.5	12.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>24.9</b>	24.7	24.3
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	3	4
Boron	ppm	ASTM D5185m	0	<b>10</b>	11	12
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>64</b>	58	58
Manganese	ppm	ASTM D5185m	0	<b>1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>902</b>	820	823
Calcium	ppm	ASTM D5185m	1070	<b>1318</b>	1201	1277
Phosphorus	ppm	ASTM D5185m	1150	<b>951</b>	887	868
Zinc	ppm	ASTM D5185m	1270	<b>1210</b>	1095	1134
Sulfur	ppm	ASTM D5185m	2060	<b>2610</b>	2310	2547
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>22.6</b>	21.8	21.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>5.9</b>	5.6	5.2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.8</b>	13.9	13.9


**FT-IR (Direct Trend)**




**Ferrous Alloys**




**Base Number**




**Non-ferrous Metals**




**Viscosity @ 100°C**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0111522  
**Lab Number** : 06158884  
**Unique Number** : 10994307  
**Test Package** : FLEET

**Received** : 24 Apr 2024  
**Tested** : 25 Apr 2024  
**Diagnosed** : 25 Apr 2024 - Wes Davis

**GFL Environmental - 074 - Douglas - Transwaste**  
 1219 Landfill Road  
 Douglas, GA  
 US 31533

Contact: CURTIS JACOBS  
 CURTIS.JACOBS@GFLENV.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: