



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

[W8794]

Machine Id

JOHN DEERE 750L 1DW750LXANF429592

Component

Hydraulic System

Fluid

JOHN DEERE HYDRAU (26 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: W8794)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0197192	JR0179155	JR0180095
Sample Date		Client Info		19 Apr 2024	11 Dec 2023	20 Sep 2023
Machine Age	hrs	Client Info		2968	2487	1977
Oil Age	hrs	Client Info		2458	0	1977
Filter Age	hrs	Client Info		1400	0	1977
Oil Changed		Client Info		Not Chngd	Not Chngd	Changed
Filter Changed		Client Info		Not Chngd	Not Chngd	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
Iron	ppm	ASTM D5185m	>20	3	1	4
Chromium	ppm	ASTM D5185m	>10	0	0	<1
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	1	2
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>75	0	<1	1
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	3	3	5
Potassium	ppm	ASTM D5185m	>20	0	<1	2
Water		WC Method	>0.1	NEG	NEG	NEG
Particles >4µm		ASTM D7647	>5000	865	921	2394
Particles >6µm		ASTM D7647	>1300	222	180	202
Particles >14µm		ASTM D7647	>160	22	15	17
Particles >21µm		ASTM D7647	>40	5	6	5
Particles >38µm		ASTM D7647	>10	0	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	17/15/12	17/15/11	18/15/11
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<1	<1	3
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		<1	0	1
Calcium	ppm	ASTM D5185m	87	87	78	86
Phosphorus	ppm	ASTM D5185m	727	662	679	631
Zinc	ppm	ASTM D5185m	900	859	864	858
Sulfur	ppm	ASTM D5185m	1500	1831	1644	1689
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.75	0.66	0.68
Visc @ 40°C	cSt	ASTM D445	65	58.5	59.5	56.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0197192 **Received** : 24 Apr 2024
Lab Number : 06158993 **Tested** : 25 Apr 2024
Unique Number : 10994416 **Diagnosed** : 25 Apr 2024 - Don Baldrige
Test Package : MOBCE (Additional Tests: PQ)

JRE - HOPE MILLS/FAYETTEVILLE
 5039 HWY 301 SOUTH
 HOPE MILLS, NC
 US 28348
 Contact: FAYETTEVILLE SHOP
 stephen.mullis@jamesriverequipment.com; panastasio@wearcheck.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)