



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
VOLVO SD115B 236554
Component
Diesel Engine
Fluid
VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (--- GAL)

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP435820	VCP414211	VCP386103
Sample Date		Client Info		13 Feb 2024	31 Jul 2023	13 Sep 2022
Machine Age	hrs	Client Info		5960	5182	4714
Oil Age	hrs	Client Info		0	0	500
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	15	29	36
Chromium	ppm	ASTM D5185m	>10	<1	3	4
Nickel	ppm	ASTM D5185m	>10	0	<1	0
Titanium	ppm	ASTM D5185m		<1	18	9
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	3	8	4
Lead	ppm	ASTM D5185m	>20	0	<1	<1
Copper	ppm	ASTM D5185m	>15	<1	3	5
Tin	ppm	ASTM D5185m	>10	0	1	2
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION













Fuel content negligible. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	6	9	19
Potassium	ppm	ASTM D5185m	>20	4	4	3
Fuel	%	ASTM D3524	>6.0	0.9	▲ 6.8	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	0.5	0.6
Nitration	Abs/cm	*ASTM D7624	>20	7.7	9.7	10.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.0	21.1	22.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<1	0	2
Boron	ppm	ASTM D5185m	2.5	13	25	18
Barium	ppm	ASTM D5185m	0.0	0	2	0
Molybdenum	ppm	ASTM D5185m	0.7	65	36	42
Manganese	ppm	ASTM D5185m	0.0	0	<1	<1
Magnesium	ppm	ASTM D5185m	256	755	487	589
Calcium	ppm	ASTM D5185m	2057	1472	1490	1549
Phosphorus	ppm	ASTM D5185m	935	1085	896	961
Zinc	ppm	ASTM D5185m	1223	1339	1083	1156
Sulfur	ppm	ASTM D5185m	4079	4124	2964	3231
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.2	19.5	20.4
Base Number (BN)	mg KOH/g	ASTM D2896	10	8.6	9.2	11.1
Visc @ 100°C	cSt	ASTM D445	15.0	13.5	▲ 11.7	12.6



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP435820 **Received** : 25 Apr 2024
Lab Number : 06160010 **Tested** : 29 Apr 2024
Unique Number : 10995433 **Diagnosed** : 29 Apr 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: PercentFuel, TBN)

RIPA AND ASSOCIATES
 10149 FISHER AVENUE
 TAMPA, FL
 US 33619
 Contact: PM Services
 PMServices@ripaconstruction.com
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)