



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR A934C-HD-ERC-LI C-50 (S/N 060798-1419)
Component
Diesel Engine
Fluid
CONOCO PHILLIPS GUARDOL ECT 15W40 (8 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0920309	WC0899830	WC0869321
Sample Date		Client Info		16 Apr 2024	04 Mar 2024	02 Nov 2023
Machine Age	hrs	Client Info		23905	23618	22950
Oil Age	hrs	Client Info		2538	388	345
Filter Age	hrs	Client Info		2538	388	345
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	SEVERE

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>66	3	6	15
Chromium	ppm	ASTM D5185m	>4	0	0	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		87	83	75
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>8	<1	1	2
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm	ASTM D5185m	>74	0	<1	1
Tin	ppm	ASTM D5185m	>4	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	1	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>15	8	7	8
Potassium	ppm	ASTM D5185m	>20	1	1	5
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	2.7	2.6	▲ 5.9
Nitration	Abs/cm	*ASTM D7624	>20	9.0	9.5	12.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.6	24.7	31.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<1	2	0
Boron	ppm	ASTM D5185m	85	99	72	62
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	<1	13
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	350	432	403	523
Calcium	ppm	ASTM D5185m	1800	1843	1860	1618
Phosphorus	ppm	ASTM D5185m	1000	1040	991	959
Zinc	ppm	ASTM D5185m	1100	1231	1170	1177
Sulfur	ppm	ASTM D5185m	3500	4159	4069	3452
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.6	15.5	17.2
Base Number (BN)	mg KOH/g	ASTM D2896	9.5	6.5	5.6	▲ 0.0
Visc @ 100°C	cSt	ASTM D445	15.3	15.5	15.4	▲ 18.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0920309
Lab Number : 06160095
Unique Number : 10995518
Test Package : CONST (Additional Tests: TBN)

FRANKLIN IRON & METAL CORP
 1939 EAST 1ST ST
 DAYTON, OH
 US 45403
 Contact: BILL PITTL JR
 parts@frankliniron.com
 T: (937)253-8184
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)