



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
Store 9 - Marietta [150126]

Machine Id
JOHN DEERE 60G 1FF060GXPDJ285425

Component
Diesel Engine

Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (12 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0047569	LEC0019581	LECP152307
Sample Date		Client Info		23 Apr 2024	04 May 2021	23 Mar 2015
Machine Age	hrs	Client Info		3756	2606	503
Oil Age	hrs	Client Info		1150	0	503
Filter Age	hrs	Client Info		0	0	503
Oil Changed		Client Info		Not Changd	Changed	Changed
Filter Changed		Client Info		Not Changd	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	10	26	50
Chromium	ppm	ASTM D5185m	>11	<1	1	1
Nickel	ppm	ASTM D5185m	>5	<1	1	<1
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	3	9	6
Lead	ppm	ASTM D5185m	>26	<1	<1	<1
Copper	ppm	ASTM D5185m	>26	1	3	6
Tin	ppm	ASTM D5185m	>4	1	1	1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>120	8	18	37
Potassium	ppm	ASTM D5185m	>20	8	1	2
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.4	0
Nitration	Abs/cm	*ASTM D7624	>20	9.4	10.8	8.
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.1	24.4	19.
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	1	0	8
Boron	ppm	ASTM D5185m		166	242	154
Barium	ppm	ASTM D5185m		1	0	0
Molybdenum	ppm	ASTM D5185m		19	85	6
Manganese	ppm	ASTM D5185m		<1	<1	2
Magnesium	ppm	ASTM D5185m		72	368	15
Calcium	ppm	ASTM D5185m		2109	1556	2606
Phosphorus	ppm	ASTM D5185m		928	963	1168
Zinc	ppm	ASTM D5185m		1148	1179	1267
Sulfur	ppm	ASTM D5185m		3545	2790	1486
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.9	22.1	15.
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	6.8	7.2	11.25
Visc @ 100°C	cSt	ASTM D445	15.4	14.5	14.0	10.12



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0047569 **Received** : 26 Apr 2024
Lab Number : 06161303 **Tested** : 28 Apr 2024
Unique Number : 10996726 **Diagnosed** : 29 Apr 2024 - Doug Bogart
Test Package : CONST (Additional Tests: TBN)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (740)373-5570