



WEAR	<b>ABNORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**KUBOTA E242**  
Component  
**Transmission (Manual)**  
Fluid  
**SUPER UDT2 (--- GAL)**

### RECOMMENDATION

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

### WEAR

Moderate concentration of visible metal present. All component wear rates are normal.







### CONTAMINATION

There is no indication of any contamination in the fluid.

### FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>JR0206142</b>	---	---
Sample Date		Client Info		<b>23 Apr 2024</b>	---	---
Machine Age	hrs	Client Info		<b>680</b>	---	---
Oil Age	hrs	Client Info		<b>200</b>	---	---
Filter Age	hrs	Client Info		<b>200</b>	---	---
Oil Changed		Client Info		<b>Changed</b>	---	---
Filter Changed		Client Info		<b>Changed</b>	---	---
Sample Status				<b>ABNORMAL</b>	---	---
PQ		ASTM D8184	>95	<b>65</b>	---	---
Iron	ppm	ASTM D5185m	>200	<b>22</b>	---	---
Chromium	ppm	ASTM D5185m	>5	<b>1</b>	---	---
Nickel	ppm	ASTM D5185m	>5	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	---	---
Silver	ppm	ASTM D5185m	>7	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m	>25	<b>6</b>	---	---
Lead	ppm	ASTM D5185m	>45	<b>1</b>	---	---
Copper	ppm	ASTM D5185m	>225	<b>1</b>	---	---
Tin	ppm	ASTM D5185m	>10	<b>1</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	---	---
White Metal	scalar	*Visual	NONE	<b>▲ MODER</b>	---	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---
Silicon	ppm	ASTM D5185m	>125	<b>36</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>4</b>	---	---
Water		WC Method	>0.1	<b>NEG</b>	---	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	---	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	---	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	---	---
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	---	---
Sodium	ppm	ASTM D5185m		<b>6</b>	---	---
Boron	ppm	ASTM D5185m		<b>0</b>	---	---
Barium	ppm	ASTM D5185m		<b>1</b>	---	---
Molybdenum	ppm	ASTM D5185m		<b>2</b>	---	---
Manganese	ppm	ASTM D5185m		<b>6</b>	---	---
Magnesium	ppm	ASTM D5185m		<b>9</b>	---	---
Calcium	ppm	ASTM D5185m		<b>3106</b>	---	---
Phosphorus	ppm	ASTM D5185m		<b>689</b>	---	---
Zinc	ppm	ASTM D5185m		<b>779</b>	---	---
Sulfur	ppm	ASTM D5185m		<b>2716</b>	---	---
Visc @ 40°C	cSt	ASTM D445		<b>32.8</b>	---	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : JR0206142

**Lab Number** : 06174102

**Unique Number** : 11020155

**Test Package** : CONST ( Additional Tests: PQ )

**Received** : 09 May 2024

**Tested** : 12 May 2024

**Diagnosed** : 12 May 2024 - Don Baldrige

**MATTHEWS CONSTRUCTION**

127 GRAYSON RD

ROCK HILL, SC

US 29732

Contact: Tad Clinton

tcClinton@matthewsconstructionco.com

T: (803)207-5607

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)