



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**ELEANOR G MCDONALD**  
Machine Id  
**[ELEANOR G MCDONALD] 004 552824-4**  
Component  
**Port Reduction Gear**  
Fluid  
**CHEVRON MEROPA 320 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0065841</b>	MW0065842	MW0065701
Sample Date		Client Info		<b>01 May 2024</b>	01 Apr 2024	05 Mar 2024
Machine Age	hrs	Client Info		<b>181254</b>	180572	179962
Oil Age	hrs	Client Info		<b>14035</b>	13333	12723
Filter Age	hrs	Client Info		<b>14035</b>	0	12723
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>N/A</b>	None	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	<b>72</b>	74	64
Chromium	ppm	ASTM D5185m	>10	<b>0</b>	<1	0
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>&lt;1</b>	<1	1
Lead	ppm	ASTM D5185m	>100	<b>20</b>	19	18
Copper	ppm	ASTM D5185m	>50	<b>6</b>	5	5
Tin	ppm	ASTM D5185m	>10	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>4</b>	4	4
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	0	2
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>14</b>	13	12
Boron	ppm	ASTM D5185m	20	<b>14</b>	11	31
Barium	ppm	ASTM D5185m		<b>8</b>	9	8
Molybdenum	ppm	ASTM D5185m	0	<b>1</b>	<1	3
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	1	<1
Magnesium	ppm	ASTM D5185m		<b>13</b>	<1	10
Calcium	ppm	ASTM D5185m	25	<b>44</b>	29	210
Phosphorus	ppm	ASTM D5185m	235	<b>310</b>	305	355
Zinc	ppm	ASTM D5185m		<b>14</b>	3	69
Sulfur	ppm	ASTM D5185m		<b>7291</b>	7136	6655
Acid Number (AN)	mg KOH/g	ASTM D8045	0.56	<b>0.54</b>	0.63	0.61
Visc @ 40°C	cSt	ASTM D445	304	<b>312</b>	314	293



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : MW0065841

**Lab Number** : 06174692

**Unique Number** : 11020745

**Test Package** : MAR 2

**Received** : 09 May 2024

**Tested** : 10 May 2024

**Diagnosed** : 10 May 2024 - Wes Davis

**INGRAM BARGE**

900 S 3RD ST

PADUCAH, KY

US 42003

Contact: ANTHONY VAN CURA

anthony.vancura@ingrambarga.com

T: (270)415-4467

F: (615)695-3697

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)