



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
KENWORTH TRACTOR 74
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LP0001035	LP0000331	WC0569990
Sample Date		Client Info		25 Apr 2024	16 May 2023	07 Apr 2022
Machine Age	hrs	Client Info		7506	16431	7455
Oil Age	hrs	Client Info		500	500	500
Filter Age	hrs	Client Info		500	500	500
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	ATTENTION

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>165	55	89	148
Chromium	ppm	ASTM D5185m	>5	<1	2	6
Nickel	ppm	ASTM D5185m	>4	0	<1	0
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	4	9	14
Lead	ppm	ASTM D5185m	>150	<1	<1	4
Copper	ppm	ASTM D5185m	>90	0	0	2
Tin	ppm	ASTM D5185m	>5	<1	1	1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>35	10	18	28
Potassium	ppm	ASTM D5185m	>20	<1	4	5
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	0.1	0.3	1.7
Nitration	Abs/cm	*ASTM D7624	>20	4.8	5.9	13.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	16.9	18.5	25.0
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	2	4	8
Boron	ppm	ASTM D5185m	250	8	15	5
Barium	ppm	ASTM D5185m	10	0	0	0
Molybdenum	ppm	ASTM D5185m	100	58	60	61
Manganese	ppm	ASTM D5185m		<1	<1	2
Magnesium	ppm	ASTM D5185m	450	896	981	974
Calcium	ppm	ASTM D5185m	3000	1075	1079	1088
Phosphorus	ppm	ASTM D5185m	1150	1105	1067	1046
Zinc	ppm	ASTM D5185m	1350	1249	1320	1316
Sulfur	ppm	ASTM D5185m	4250	3820	4057	2482
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.0	14.0	22.0
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	9.81	10.23	8.61
Visc @ 100°C	cSt	ASTM D445	14.4	14.5	14.0	13.5



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LP0001035
Lab Number : 06174735
Unique Number : 11020788
Test Package : MOB 2

Received : 09 May 2024
Tested : 10 May 2024
Diagnosed : 10 May 2024 - Wes Davis

TRESCA BROS SAND & GRAVEL INC
 66 MAIN ST
 MILLIS, MA
 US 02054
 Contact: JACK GALIANO
 jgaliano@trescaconcrete.com
 T: (508)376-2957
 F: (508)376-4333

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)