



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**529013**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0091858</b>	GFL0061028	GFL0112769
Sample Date		Client Info		<b>02 May 2024</b>	12 Feb 2024	07 Feb 2024
Machine Age	hrs	Client Info		<b>11239</b>	12000	11112
Oil Age	hrs	Client Info		<b>11239</b>	610	10688
Filter Age	hrs	Client Info		<b>0</b>	610	0
Oil Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Filter Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>110	<b>24</b>	38	13
Chromium	ppm	ASTM D5185m	>4	<b>&lt;1</b>	1	<1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	<1
Aluminum	ppm	ASTM D5185m	>25	<b>2</b>	4	1
Lead	ppm	ASTM D5185m	>45	<b>0</b>	3	0
Copper	ppm	ASTM D5185m	>85	<b>2</b>	2	1
Tin	ppm	ASTM D5185m	>4	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	<b>9</b>	4	6
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	4	1
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.6</b>	0.8	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.3</b>	10.4	8.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>20.3</b>	21.3	19.3
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>1</b>	2	<1
Boron	ppm	ASTM D5185m	0	<b>&lt;1</b>	6	2
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>65</b>	61	60
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>996</b>	879	1026
Calcium	ppm	ASTM D5185m	1070	<b>1145</b>	1000	1074
Phosphorus	ppm	ASTM D5185m	1150	<b>1146</b>	941	1068
Zinc	ppm	ASTM D5185m	1270	<b>1316</b>	1206	1299
Sulfur	ppm	ASTM D5185m	2060	<b>3165</b>	2691	3122
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>16.6</b>	18.1	15.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.2</b>	4.8	8.5
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.3</b>	12.6	14.3



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0091858  
**Lab Number** : 06174860  
**Unique Number** : 11020913  
**Test Package** : FLEET  
**Received** : 09 May 2024  
**Tested** : 10 May 2024  
**Diagnosed** : 10 May 2024 - Wes Davis

**GFL Environmental - 654 - Richmond Hauling**  
 11800 Lewis Road  
 Chester, VA  
 US 23831  
 Contact: Jimmy Mayes  
 jmayes@gflenv.com  
 T:  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)