



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
4481L
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		IL0032480	IL06175099	IL0034338
Sample Date		Client Info		18 Apr 2024	12 Apr 2024	23 Jan 2024
Machine Age	mls	Client Info		255170	0	243126
Oil Age	mls	Client Info		15000	15000	15000
Filter Age	mls	Client Info		15000	0	15000
Oil Changed		Client Info		Changed	N/A	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	80	23	41
Chromium	ppm	ASTM D5185m	>20	2	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	10	3	7
Lead	ppm	ASTM D5185m	>40	<1	0	0
Copper	ppm	ASTM D5185m	>330	0	<1	2
Tin	ppm	ASTM D5185m	>15	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	5	3	7
Potassium	ppm	ASTM D5185m	>20	19	4	4
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1.5	0.3	1
Nitration	Abs/cm	*ASTM D7624	>20	15.0	10.7	15.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	31.9	21.9	29.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	2	1	1
Boron	ppm	ASTM D5185m	250	<1	0	2
Barium	ppm	ASTM D5185m	10	0	0	0
Molybdenum	ppm	ASTM D5185m	100	56	65	64
Manganese	ppm	ASTM D5185m		1	<1	<1
Magnesium	ppm	ASTM D5185m	450	850	1029	1043
Calcium	ppm	ASTM D5185m	3000	1023	1170	1133
Phosphorus	ppm	ASTM D5185m	1150	933	1083	1125
Zinc	ppm	ASTM D5185m	1350	1107	1307	1423
Sulfur	ppm	ASTM D5185m	4250	3324	3495	3266
Oxidation	Abs/.1mm	*ASTM D7414	>25	35.8	21.6	31.0
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	4.7	7.0	4.6
Visc @ 100°C	cSt	ASTM D445	14.4	12.5	12.3	14.0


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : IL0032480

Lab Number : 06175174

Unique Number : 11021227

Test Package : FLEET

Received : 10 May 2024

Tested : 11 May 2024

Diagnosed : 13 May 2024 - Don Baldrige

RUSH TRUCK CENTER - CHICAGO IDEALEASE

4655 SOUTH CENTRAL AVENUE

CHICAGO, IL

US 60638

Contact: MIKE LINLEY

linleym@rushtruckcenters.com

T: (708)496-7500

F: (708)496-8818

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)