



VOLVO

OIL ANALYSIS REPORT

WEAR	ABNORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area

[42079]

Machine Id

VOLVO A45G 352596

Component

Diesel Engine

Fluid

VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (--- GAL)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP453821	VCP454617	VCP407066
Sample Date		Client Info		08 May 2024	29 Mar 2024	11 Sep 2023
Machine Age	hrs	Client Info		5998	5825	5818
Oil Age	hrs	Client Info		0	6	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	N/A
Filter Changed		Client Info		Changed	Not Changd	N/A
Sample Status				ABNORMAL	NORMAL	NORMAL

WEAR

Valve wear is indicated. All other component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	8	6	17
Chromium	ppm	ASTM D5185m	>20	0	0	1
Nickel	ppm	ASTM D5185m	>2	▲ 10	6	6
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	3	2	3
Lead	ppm	ASTM D5185m	>40	<1	0	<1
Copper	ppm	ASTM D5185m	>330	6	5	17
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.













Silicon	ppm	ASTM D5185m	>25	6	9	6
Potassium	ppm	ASTM D5185m	>20	0	0	0
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	0.1	0.5
Nitration	Abs/cm	*ASTM D7624	>20	6.3	5.1	7.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.7	21.4	18.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	3	6
Boron	ppm	ASTM D5185m	2.5	56	64	13
Barium	ppm	ASTM D5185m	0.0	0	0	0
Molybdenum	ppm	ASTM D5185m	0.7	41	39	59
Manganese	ppm	ASTM D5185m	0.0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	256	550	559	864
Calcium	ppm	ASTM D5185m	2057	1594	1513	1109
Phosphorus	ppm	ASTM D5185m	935	952	948	967
Zinc	ppm	ASTM D5185m	1223	1084	1093	1144
Sulfur	ppm	ASTM D5185m	4079	3352	3496	2864
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.8	18.5	13.5
Base Number (BN)	mg KOH/g	ASTM D2896	10	10.4	10.5	6.5
Visc @ 100°C	cSt	ASTM D445	15.0	12.5	12.9	13.2

▲ Ferrous Alloys



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP453821 **Received** : 10 May 2024
Lab Number : 06175213 **Tested** : 13 May 2024
Unique Number : 11021266 **Diagnosed** : 13 May 2024 - Don Baldrige
Test Package : MOB 1 (Additional Tests: TBN)

LANDMARK CONSTRUCTION CO. INC./MEM
 3255 INDUSTRY DRIVE
 NORTH CHARLESTON, SC
 US 29418
 Contact: GENE RICHARDSON
 grichardson@landmark-sc.com
 T: (843)767-9741
 F: (843)767-9909

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)