



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

Current

Machine Id

IC 03-22

Component

Forward Diesel Engine

Fluid

DIESEL ENGINE OIL SAE 10W30 (19 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0849362	WC0693101	WC0693055
Sample Date		Client Info		06 May 2024	23 May 2023	27 May 2022
Machine Age	mls	Client Info		35887	24812	12249
Oil Age	mls	Client Info		11075	12563	12249
Filter Age	mls	Client Info		11075	12563	12249
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ATTENTION	ABNORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>130	45	71	117
Chromium	ppm	ASTM D5185m	>10	2	2	3
Nickel	ppm	ASTM D5185m	>4	0	<1	0
Titanium	ppm	ASTM D5185m	>2	0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	35	54	45
Lead	ppm	ASTM D5185m	>20	<1	0	<1
Copper	ppm	ASTM D5185m	>125	4	12	74
Tin	ppm	ASTM D5185m	>4	0	<1	2
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	12	20	▲ 54
Potassium	ppm	ASTM D5185m	>20	72	129	162
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	0.7	0.8	0.8
Nitration	Abs/cm	*ASTM D7624	>20	10.1	11.6	14.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.9	27.6	25.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	4	7
Boron	ppm	ASTM D5185m	250	11	1	29
Barium	ppm	ASTM D5185m	10	<1	0	7
Molybdenum	ppm	ASTM D5185m	100	6	4	44
Manganese	ppm	ASTM D5185m		<1	2	7
Magnesium	ppm	ASTM D5185m	450	42	65	696
Calcium	ppm	ASTM D5185m	3000	2384	2321	1327
Phosphorus	ppm	ASTM D5185m	1150	894	860	730
Zinc	ppm	ASTM D5185m	1350	1067	1046	957
Sulfur	ppm	ASTM D5185m	4250	3904	3460	2377
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.9	19.0	25.1
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	5.05	5.98	7.03
Visc @ 100°C	cSt	ASTM D445	10.9	10.9	● 11.0	● 11.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0849362
Lab Number : 06176261
Unique Number : 11022314
Test Package : MOB 2

Received : 10 May 2024
Tested : 13 May 2024
Diagnosed : 13 May 2024 - Wes Davis

INDIANOLA COMMUNITY SCHOOL DISTRICT
 1206 EAST ASHLAND, ATTN: JASON LOGAN
 INDIANOLA, IA
 US 50125
 Contact: JASON LOGAN
 loganj@indianola.k12.ia.us
 T: (515)961-9592
 F: (515)961-9504

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)