



OIL ANALYSIS REPORT

| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
E-ONE LADDER 28
 Component
Hydraulic System
 Fluid
AW HYDRAULIC OIL ISO 32 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | WC0917795 | WC0697322 | WC0499304 |
| Sample Date | | Client Info | | 05 Apr 2024 | 25 May 2022 | 06 Jun 2021 |
| Machine Age | mls | Client Info | | 0 | 0 | 0 |
| Oil Age | mls | Client Info | | 0 | 0 | 0 |
| Filter Age | mls | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | Not Chngd | N/A | N/A |
| Filter Changed | | Client Info | | Not Chngd | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|-------------|------|------|
| Iron | ppm | ASTM D5185m | >20 | 4 | 6 | 6 |
| Chromium | ppm | ASTM D5185m | >10 | 0 | 0 | <1 |
| Nickel | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m | | 0 | <1 | 0 |
| Aluminum | ppm | ASTM D5185m | >10 | 0 | <1 | <1 |
| Lead | ppm | ASTM D5185m | >10 | 0 | <1 | <1 |
| Copper | ppm | ASTM D5185m | >75 | 35 | 34 | 34 |
| Tin | ppm | ASTM D5185m | >10 | 0 | <1 | <1 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION





There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|--------|-------------|-------|--------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >20 | 4 | 4 | 4 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | 1 | 0 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | VLITE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | NEG |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|-------------|-----|-------------|------|--------------|------|------|
| Sodium | ppm | ASTM D5185m | | 2 | 0 | 2 |
| Boron | ppm | ASTM D5185m | 5 | <1 | 4 | 5 |
| Barium | ppm | ASTM D5185m | 5 | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 5 | 0 | 1 | 1 |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Magnesium | ppm | ASTM D5185m | 25 | 9 | 13 | 15 |
| Calcium | ppm | ASTM D5185m | 200 | 155 | 139 | 153 |
| Phosphorus | ppm | ASTM D5185m | 300 | 309 | 290 | 297 |
| Zinc | ppm | ASTM D5185m | 370 | 354 | 351 | 370 |
| Sulfur | ppm | ASTM D5185m | 2500 | 1750 | 1456 | 1417 |
| Visc @ 40°C | cSt | ASTM D445 | 32 | 34.6 | 34.5 | 34.6 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0917795
Lab Number : 06176372
Unique Number : 11022425
Test Package : FLEET
Received : 10 May 2024
Tested : 13 May 2024
Diagnosed : 13 May 2024 - Wes Davis

ANDERSON FIRE DEPT
 400 S MCDUFFIE
 ANDERSON, SC
 US 29624
 Contact: JEFF CARNES
 jcarnes@acfd.org
 T: (864)260-4016
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)