



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
804BL
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (20 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		IL0036541	IL0031126	IL0026941
Sample Date		Client Info		12 May 2024	18 Aug 2023	26 Sep 2022
Machine Age	mls	Client Info		101897	86777	77406
Oil Age	mls	Client Info		15120	10371	12713
Filter Age	mls	Client Info		15120	10371	12713
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	49	88	51
Chromium	ppm	ASTM D5185m	>20	1	2	1
Nickel	ppm	ASTM D5185m	>4	<1	<1	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	16	18	11
Lead	ppm	ASTM D5185m	>40	<1	0	0
Copper	ppm	ASTM D5185m	>330	3	4	2
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	7	8	7
Potassium	ppm	ASTM D5185m	>20	11	10	12
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol	%	*ASTM D2982		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.9	1.3	1
Nitration	Abs/cm	*ASTM D7624	>20	12.0	13.0	12.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.2	25.5	24.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	0	4	2
Boron	ppm	ASTM D5185m	250	3	6	31
Barium	ppm	ASTM D5185m	10	2	<1	0
Molybdenum	ppm	ASTM D5185m	100	69	63	46
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m	450	895	959	516
Calcium	ppm	ASTM D5185m	3000	1112	1247	1739
Phosphorus	ppm	ASTM D5185m	1150	1043	989	765
Zinc	ppm	ASTM D5185m	1350	1197	1250	946
Sulfur	ppm	ASTM D5185m	4250	3218	3512	2996
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.9	22.1	25.2
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	7.5	6.1	10.1
Visc @ 100°C	cSt	ASTM D445	14.4	12.6	13.6	13.1


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Glycol Contamination




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : IL0036541 **Received** : 10 May 2024
Lab Number : 06176497 **Tested** : 14 May 2024
Unique Number : 11022550 **Diagnosed** : 14 May 2024 - Sean Felton
Test Package : FLEET (Additional Tests: Glycol)

RUSH TRUCK LEASING - CLEVELAND IDEALEASE
 5 ACORN DR
 OAKWOOD VILLAGE, OH
 US 44146-5550
 Contact: JOHN FOSTER
 FosterJ4@RushEnterprises.com
 T: (440)359-7000
 F: (440)439-5657

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)