



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area

(ECY338)

Machine Id

**AUTOCAR 3742**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (10 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0116812</b>	GFL0116799	GFL0116734
Sample Date		Client Info		<b>09 May 2024</b>	24 Apr 2024	19 Mar 2024
Machine Age	hrs	Client Info		<b>19224</b>	19121	18808
Oil Age	hrs	Client Info		<b>3482</b>	3379	3066
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	Not Changd	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>165	<b>23</b>	18	9
Chromium	ppm	ASTM D5185m	>5	<b>2</b>	1	<1
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>1</b>	<1	1
Lead	ppm	ASTM D5185m	>150	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m	>90	<b>3</b>	<1	4
Tin	ppm	ASTM D5185m	>5	<b>&lt;1</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>35	<b>5</b>	4	4
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	0	0
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	<b>0.8</b>	0.7	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>8.1</b>	7.2	7.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.1</b>	18.6	18.0
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	4	2
Boron	ppm	ASTM D5185m	0	<b>9</b>	7	8
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>59</b>	60	59
Manganese	ppm	ASTM D5185m	0	<b>1</b>	<1	0
Magnesium	ppm	ASTM D5185m	1010	<b>854</b>	844	864
Calcium	ppm	ASTM D5185m	1070	<b>1112</b>	1130	1193
Phosphorus	ppm	ASTM D5185m	1150	<b>985</b>	989	1028
Zinc	ppm	ASTM D5185m	1270	<b>1175</b>	1185	1199
Sulfur	ppm	ASTM D5185m	2060	<b>3218</b>	3432	3656
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.9</b>	13.2	13.5
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.3</b>	7.6	7.9
Visc @ 100°C	cSt	ASTM D445	15.4	<b>12.6</b>	12.6	12.6


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0116812  
**Lab Number** : 06176735  
**Unique Number** : 11022788  
**Test Package** : FLEET

**Received** : 13 May 2024  
**Tested** : 14 May 2024  
**Diagnosed** : 14 May 2024 - Wes Davis

**GFL Environmental - 009 - Fairburn**  
 6905 Roosevelt Hwy  
 Fairburn, GA  
 US 30213  
 Contact: Eric Jones  
 erjones@gflenv.com  
 T: (678)630-9927  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)