



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
834094
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON GEO LD 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0118790	GFL0118758	GFL0114110
Sample Date		Client Info		08 May 2024	15 Apr 2024	18 Mar 2024
Machine Age	hrs	Client Info		1146	998	860
Oil Age	hrs	Client Info		1146	998	716
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	63	64	53
Chromium	ppm	ASTM D5185m	>20	3	3	2
Nickel	ppm	ASTM D5185m	>4	2	3	2
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m	>3	0	<1	0
Aluminum	ppm	ASTM D5185m	>20	34	32	27
Lead	ppm	ASTM D5185m	>40	1	2	2
Copper	ppm	ASTM D5185m	>330	18	19	15
Tin	ppm	ASTM D5185m	>15	2	2	2
Vanadium	ppm	ASTM D5185m		0	<1	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION









Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	24	27	24
Potassium	ppm	ASTM D5185m	>20	119	115	113
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0
Nitration	Abs/cm	*ASTM D7624	>20	12.7	12.5	12.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	26.0	25.8	24.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		8	5	8
Boron	ppm	ASTM D5185m	50	10	7	10
Barium	ppm	ASTM D5185m	5	<1	3	2
Molybdenum	ppm	ASTM D5185m	50	66	65	58
Manganese	ppm	ASTM D5185m	0	14	14	12
Magnesium	ppm	ASTM D5185m	560	832	746	720
Calcium	ppm	ASTM D5185m	1510	1447	1292	1286
Phosphorus	ppm	ASTM D5185m	780	817	820	706
Zinc	ppm	ASTM D5185m	870	1027	970	885
Sulfur	ppm	ASTM D5185m	2040	2719	2651	2553
Oxidation	Abs/.1mm	*ASTM D7414	>25	23.3	23.2	21.9
Base Number (BN)	mg KOH/g	ASTM D2896	10.2	3.2	▲ 1.9	3.5
Visc @ 100°C	cSt	ASTM D445	15.1	14.3	14.2	14.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0118790
Lab Number : 06176741
Unique Number : 11022794
Test Package : FLEET

GFL Environmental - 837 - Harrison TS
 22820 S State Route 291
 Harrisonville, MO
 US 64701
 Contact: SARA PATRICK
 spatrick@gflenv.com
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)