



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**720026-37**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0121134</b>	GFL0103119	GFL0091983
Sample Date		Client Info		<b>10 May 2024</b>	09 Feb 2024	20 Nov 2023
Machine Age	hrs	Client Info		<b>6538</b>	6073	5780
Oil Age	hrs	Client Info		<b>465</b>	293	575
Filter Age	hrs	Client Info		<b>465</b>	293	575
Oil Changed		Client Info		<b>N/A</b>	Changed	Changed
Filter Changed		Client Info		<b>N/A</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	<b>11</b>	6	14
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	2	2
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	<1	<1
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	1	2
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	<b>4</b>	4	6
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	2	2
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>6	<b>0.4</b>	0.2	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>8.6</b>	7.6	8.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.5</b>	18.7	19.3
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>5</b>	<1	6
Boron	ppm	ASTM D5185m	0	<b>11</b>	2	2
Barium	ppm	ASTM D5185m	0	<b>0</b>	13	0
Molybdenum	ppm	ASTM D5185m	60	<b>63</b>	54	60
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>996</b>	822	1035
Calcium	ppm	ASTM D5185m	1070	<b>1133</b>	946	1109
Phosphorus	ppm	ASTM D5185m	1150	<b>1065</b>	967	1045
Zinc	ppm	ASTM D5185m	1270	<b>1331</b>	1071	1318
Sulfur	ppm	ASTM D5185m	2060	<b>3585</b>	3254	3211
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>16.0</b>	15.2	15.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.5</b>	8.7	8.4
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	13.0	13.6


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0121134  
**Lab Number** : 06176883  
**Unique Number** : 11022936  
**Test Package** : FLEET

**Received** : 13 May 2024  
**Tested** : 14 May 2024  
**Diagnosed** : 14 May 2024 - Wes Davis

**GFL Environmental - 683 - Ruckersville Hauling**  
 261 INDUSTRIAL DR  
 Ruckersville, VA  
 US 22698

Contact: Jaf Finney  
 jfinney@gflenv.com  
 T: (434)990-4972

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: