



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**PALEXTRA 44**  
Machine Id  
**20KE001584 - WALSH CUSTOM SURFACES**  
Component  
**Compressor**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>UCS06177337</b>	UCS05570114	UCS05502544
Sample Date		Client Info		<b>30 Apr 2024</b>	08 Jun 2022	17 Mar 2022
Machine Age	hrs	Client Info		<b>7909</b>	3575	2896
Oil Age	hrs	Client Info		<b>900</b>	3575	2896
Filter Age	hrs	Client Info		<b>900</b>	700	0
Oil Changed		Client Info		<b>Not Changed</b>	Changed	Not Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	<b>0</b>	<1	0
Chromium	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	0
Nickel	ppm	ASTM D5185m		<b>0</b>	0	2
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>2</b>	<1	<1
Lead	ppm	ASTM D5185m	>25	<b>&lt;1</b>	<1	<1
Copper	ppm	ASTM D5185m	>50	<b>&lt;1</b>	<1	3
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>4</b>	2	<1
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	<1	3
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>LIGHT</b>	NONE	MODER
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>0</b>	0	<1
Boron	ppm	ASTM D5185m	0	<b>0</b>	0	6
Barium	ppm	ASTM D5185m	0.3	<b>2</b>	0	0
Molybdenum	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	0
Manganese	ppm	ASTM D5185m	0.3	<b>0</b>	0	0
Magnesium	ppm	ASTM D5185m	0.4	<b>3</b>	<1	2
Calcium	ppm	ASTM D5185m	0	<b>7</b>	0	0
Phosphorus	ppm	ASTM D5185m	689	<b>700</b>	558	856
Zinc	ppm	ASTM D5185m	0	<b>8</b>	0	0
Sulfur	ppm	ASTM D5185m	1237	<b>1005</b>	395	949
Acid Number (AN)	mg KOH/g	ASTM D8045	0.135	<b>0.089</b>	0.26	0.34
Visc @ 40°C	cSt	ASTM D445	44.62	<b>43.2</b>	45.4	44.0



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : UCS06177337 **Received** : 13 May 2024  
**Lab Number** : 06177337 **Tested** : 14 May 2024  
**Unique Number** : 11023390 **Diagnosed** : 15 May 2024 - Don Baldrige  
**Test Package** : IND 2

**PYE-BARKER SUPPLY CO INC**

SYLVANIA, GA  
US 30467

Contact: LARRY RIVERS  
Irrivers@pyebarker.com

T: (912)425-0400

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)