



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
DE Samples - CAT LAB
Machine Id
CATERPILLAR 980H LOADER 6821 (S/N JMS06208)
Component
Rear Differential
Fluid
TULCO LUBSOIL TO-4 50 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TO10003087	TO10003144	TO10002863
Sample Date		Client Info		08 May 2024	20 Feb 2024	13 Nov 2023
Machine Age	hrs	Client Info		29374	28828	28310
Oil Age	hrs	Client Info		5765	1302	784
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	None	None
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		31	28	22
Iron	ppm	ASTM D5185m	>500	24	11	10
Chromium	ppm	ASTM D5185m	>3	<1	<1	<1
Nickel	ppm	ASTM D5185m	>3	<1	0	<1
Titanium	ppm	ASTM D5185m	>2	<1	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>30	3	2	2
Lead	ppm	ASTM D5185m	>13	<1	0	<1
Copper	ppm	ASTM D5185m	>103	3	1	1
Tin	ppm	ASTM D5185m	>5	<1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION













There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>100	23	15	16
Potassium	ppm	ASTM D5185m	>20	3	0	0
Water		WC Method	>.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	4	5
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		17	14	0
Calcium	ppm	ASTM D5185m		5001	3360	3400
Phosphorus	ppm	ASTM D5185m		1389	920	791
Zinc	ppm	ASTM D5185m		1669	1135	1107
Sulfur	ppm	ASTM D5185m		8360	4828	4352
Acid Number (AN)	mg KOH/g	ASTM D8045		1.10	1.10	1.07
Visc @ 40°C	cSt	ASTM D445		209	210	207
Visc @ 100°C	cSt	ASTM D445		18.1	18.0	18.1
Viscosity Index (VI)	Scale	ASTM D2270		94	93	95



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TO10003087
Lab Number : 06177819
Unique Number : 11029145
Test Package : MOB 2 (Additional Tests: KV100, PQ, VI)

Received : 13 May 2024
Tested : 14 May 2024
Diagnosed : 15 May 2024 - Angela Borella

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

ANCHOR STONE TULSA ROCK
 TULSA ROCK QUARRY, 66TH ST N 145TH AVENUE
 TULSA, OK
 US 74137

Contact: MIKE SNYDER
 msnyder@anchorstoneco.com
 T: (417)850-9635

F: