



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |

Area  
**MARTHA INGRAM**  
Machine Id  
[**MARTHA INGRAM**] 002 589419-2  
Component  
Center Main Engine  
Fluid  
CHEVRON DELO 710 LS (350 GAL)

**RECOMMENDATION**

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>MW0061470</b>   | MW0064317   | MW0053588   |
| Sample Date    |     | Client Info |           | <b>01 May 2024</b> | 31 Jan 2024 | 01 Aug 2023 |
| Machine Age    | hrs | Client Info |           | <b>16244</b>       | 14223       | 9994        |
| Oil Age        | hrs | Client Info |           | <b>16244</b>       | 298         | 9994        |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | 298         | 471         |
| Oil Changed    |     | Client Info |           | <b>Not Chngd</b>   | N/A         | Changed     |
| Filter Changed |     | Client Info |           | <b>Not Chngd</b>   | N/A         | Changed     |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | NORMAL      |

**WEAR**

All component wear rates are normal.

|              |        |             |      |             |      |      |
|--------------|--------|-------------|------|-------------|------|------|
| Iron         | ppm    | ASTM D5185m | >75  | <b>9</b>    | 9    | 14   |
| Chromium     | ppm    | ASTM D5185m | >8   | <b>1</b>    | <1   | 2    |
| Nickel       | ppm    | ASTM D5185m | >2   | <b>0</b>    | 0    | <1   |
| Titanium     | ppm    | ASTM D5185m | >3   | <b>0</b>    | <1   | 0    |
| Silver       | ppm    | ASTM D5185m | >2   | <b>0</b>    | 0    | 0    |
| Aluminum     | ppm    | ASTM D5185m | >15  | <b>1</b>    | 3    | 4    |
| Lead         | ppm    | ASTM D5185m | >18  | <b>4</b>    | 2    | 5    |
| Copper       | ppm    | ASTM D5185m | >80  | <b>10</b>   | 6    | 12   |
| Tin          | ppm    | ASTM D5185m | >14  | <b>4</b>    | 2    | 5    |
| Vanadium     | ppm    | ASTM D5185m |      | <b>0</b>    | <1   | <1   |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b> | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b> | NONE | NONE |

**CONTAMINATION**

There is no indication of any contamination in the oil.


|                  |          |             |       |                |       |       |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon          | ppm      | ASTM D5185m | >20   | <b>6</b>       | 4     | 5     |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>&lt;1</b>   | 2     | 2     |
| Fuel             |          | WC Method   | >4.0  | <b>&lt;1.0</b> | <1.0  | <1.0  |
| Water            |          | WC Method   | >0.1  | <b>NEG</b>     | NEG   | NEG   |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | NEG   |
| Soot %           | %        | *ASTM D7844 | >3    | <b>0.6</b>     | 0.2   | 1.2   |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>9.0</b>     | 7.1   | 9.0   |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>17.4</b>    | 14.3  | 17.8  |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Emulsified Water | scalar   | *Visual     | >0.1  | <b>NEG</b>     | NEG   | NEG   |

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

|                  |          |             |      |             |      |       |
|------------------|----------|-------------|------|-------------|------|-------|
| Sodium           | ppm      | ASTM D5185m | >75  | <b>14</b>   | <1   | 7     |
| Boron            | ppm      | ASTM D5185m |      | <b>42</b>   | 44   | 36    |
| Barium           | ppm      | ASTM D5185m |      | <b>1</b>    | 0    | 0     |
| Molybdenum       | ppm      | ASTM D5185m |      | <b>46</b>   | 48   | 49    |
| Manganese        | ppm      | ASTM D5185m |      | <b>2</b>    | <1   | <1    |
| Magnesium        | ppm      | ASTM D5185m |      | <b>12</b>   | 28   | 11    |
| Calcium          | ppm      | ASTM D5185m |      | <b>3490</b> | 3452 | 3736  |
| Phosphorus       | ppm      | ASTM D5185m |      | <b>4</b>    | 27   | 9     |
| Zinc             | ppm      | ASTM D5185m |      | <b>0</b>    | 21   | 8     |
| Sulfur           | ppm      | ASTM D5185m |      | <b>2594</b> | 2368 | 2591  |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25  | <b>8.9</b>  | 7.3  | 8.2   |
| Base Number (BN) | mg KOH/g | ASTM D2896  | 10.5 | <b>9.31</b> | 9.95 | 10.20 |
| Visc @ 100°C     | cSt      | ASTM D445   | 15.5 | <b>15.1</b> | 15.0 | 15.3  |


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : MW0061470

**Lab Number** : 06177896

**Unique Number** : 11029222

**Test Package** : MAR 2

**Received** : 13 May 2024

**Tested** : 14 May 2024

**Diagnosed** : 14 May 2024 - Wes Davis

**INGRAM BARGE**

900 S 3RD ST

PADUCAH, KY

US 42003

Contact: GLENN ELLIS

glenn.ellis@ingrambarga.com

T: (270)415-4467

F: (615)695-3697

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)