

Machine Id NO INFO 06178224 Component Diesel Engine

{not provided} (--- GAL)


	T	11014	Markle 1	1.5		L.P. A. A	
RECOMMENDATION	Test	UOM	Method	Limit/Abn	Current	History1	History2
No corrective action is recommended at this time. We recommend an early resample to monitor this condition. Please specify the brand, type, and viscosity of the oil on your next sample.	Sample Number		Client Info		WC06178224		
	Sample Date		Client Info		13 May 2024		
	Machine Age	hrs	Client Info		0		
	Oil Age	hrs	Client Info		0		
	Filter Age	hrs	Client Info		0		
	Oil Changed		Client Info		N/A		
	Filter Changed		Client Info		N/A		
	Sample Status				ABNORMAL		
WEAR	Iron	ppm	ASTM D5185m	>100	113		
	Chromium	ppm	ASTM D5185m		1		
Cylinder, crank, or cam shaft wear is indicated.	Nickel	ppm	ASTM D5185m		2		
	Titanium	ppm	ASTM D5185m		- <1		
	Silver	ppm	ASTM D5185m	>3	<1		
	Aluminum	ppm	ASTM D5185m		5		
	Lead	ppm	ASTM D5185m		2		
	Copper	ppm	ASTM D5185m		16		
	Tin	ppm	ASTM D5185m		1		
	Vanadium	ppm	ASTM D5185m	210	- <1		
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
		304141	visual	NONE			
CONTAMINATION	Silicon	ppm	ASTM D5185m		10		
Fuel content negligible. There is no indication of any contamination in the oil.	Potassium	ppm	ASTM D5185m		3		
	Fuel	%	ASTM D3524		0.6		
	Water		WC Method	>0.2	NEG		
	Glycol		WC Method		NEG		
	Soot %	%	*ASTM D7844	>3	0.6		
	Nitration	Abs/cm	*ASTM D7624		9.4		
	Sulfation	Abs/.1mm	*ASTM D7415	>30	21.5		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
	Appearance	scalar	*Visual	NORML	NORML		
	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.2	NEG		
FLUID CONDITION	Sodium	nom	ASTM D5185m		6		
	Boron	ppm	ASTM D5185m		7		
The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.	Barium	ppm	ASTM D5185m		7 <1		
	Molybdenum	ppm ppm	ASTM D5185m		67		
	Manganese		ASTM D5185m				
	Magnesium	ppm	ASTM D5185m		2 854		
	Calcium	ppm	ASTM D5185m		054 1139		
		ppm					
	Phosphorus	ppm	ASTM D5185m		955		
	Zinc	ppm	ASTM D5185m		1218		
	Sulfur	ppm	ASTM D5185m	. 05	2914		
	Oxidation	Abs/.1mm	*ASTM D7414	>25	17.7		
	Base Number (BN)	mg KOH/g	ASTM D2896		6.0		

Visc @ 100°C cSt

ASTM D445

11.3





Contact/Location: Service Manager - PERCANNC Page 2 of 2