



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**(P1059714)**

Machine Id  
**524052**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0120600</b>	GFL0108447	GFL0082371
Sample Date		Client Info		<b>06 May 2024</b>	10 Apr 2024	25 Jan 2024
Machine Age	hrs	Client Info		<b>0</b>	0	16529
Oil Age	hrs	Client Info		<b>0</b>	0	600
Filter Age	hrs	Client Info		<b>0</b>	0	600
Oil Changed		Client Info		<b>N/A</b>	N/A	Changed
Filter Changed		Client Info		<b>N/A</b>	N/A	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>4</b>	10	8
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	<1	0
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	3	<1
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>&lt;1</b>	2	2
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	1	4
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>4</b>	5	4
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	0	<1
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.1</b>	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.8</b>	5.6	6.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.3</b>	17.8	18.8
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	3	2
Boron	ppm	ASTM D5185m	0	<b>0</b>	2	33
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>60</b>	61	64
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	0
Magnesium	ppm	ASTM D5185m	1010	<b>1023</b>	982	1000
Calcium	ppm	ASTM D5185m	1070	<b>1120</b>	1158	1147
Phosphorus	ppm	ASTM D5185m	1150	<b>1073</b>	1072	1061
Zinc	ppm	ASTM D5185m	1270	<b>1245</b>	1229	1272
Sulfur	ppm	ASTM D5185m	2060	<b>3742</b>	3774	3298
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.6</b>	14.0	14.8
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.8</b>	8.8	8.5
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.3</b>	14.3	13.7



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0120600 **Received** : 14 May 2024  
**Lab Number** : 06178363 **Tested** : 14 May 2024  
**Unique Number** : 11029689 **Diagnosed** : 14 May 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 959F - Clinton HC**  
 9550 Heritage Rd  
 Clinton, IL  
 US 61727  
 Contact: Larry Siegmann  
 lsiegmann@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)