



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 350P 1FF350PALNF000408
 Component
Pump Drive
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (1 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0217918	JR0184617	JR0176186
Sample Date		Client Info		17 May 2024	29 Nov 2023	19 Jun 2023
Machine Age	hrs	Client Info		1908	1521	943
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		19	307	18
Iron	ppm	ASTM D5185m	>151	42	64	60
Chromium	ppm	ASTM D5185m	>11	1	<1	2
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		<1	0	0
Aluminum	ppm	ASTM D5185m	>21	6	3	0
Lead	ppm	ASTM D5185m	>51	<1	0	0
Copper	ppm	ASTM D5185m	>51	1	0	0
Tin	ppm	ASTM D5185m	>4	1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	LIGHT	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>31	19	18	48
Potassium	ppm	ASTM D5185m	>20	4	0	<1
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	4	2	3
Boron	ppm	ASTM D5185m		317	338	54
Barium	ppm	ASTM D5185m		0	<1	13
Molybdenum	ppm	ASTM D5185m		255	260	95
Manganese	ppm	ASTM D5185m		2	1	4
Magnesium	ppm	ASTM D5185m		780	754	21
Calcium	ppm	ASTM D5185m		1546	1671	4143
Phosphorus	ppm	ASTM D5185m		969	930	1183
Zinc	ppm	ASTM D5185m		1101	1090	1320
Sulfur	ppm	ASTM D5185m		3831	3447	9527
Visc @ 40°C	cSt	ASTM D445	117	78.8	66.0	60.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0217918 **Received** : 21 May 2024
Lab Number : 06186912 **Tested** : 23 May 2024
Unique Number : 11043664 **Diagnosed** : 23 May 2024 - Wes Davis
Test Package : CONST (Additional Tests: PQ)

JRE - MANASSAS PARK
 9107 OWENS DRIVE
 MANASSAS PARK, VA
 US 20111

Contact: DON VEST
 dvest@jamesriverequipment.com
 T: (703)631-8500
 F: (703)631-4715

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)