



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
ONE WORLD LOGISTICS
Machine Id
VOLVO OWL207125
Component
Diesel Engine
Fluid
DIESEL ENGINE OIL SAE 40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		NL0002291	NL0001755	NL0001596
Sample Date		Client Info		10 May 2024	27 Nov 2023	12 Jun 2023
Machine Age	mls	Client Info		449507	449507	449507
Oil Age	mls	Client Info		0	399552	71657
Filter Age	mls	Client Info		0	399552	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	71	49	66
Chromium	ppm	ASTM D5185m	>20	<1	<1	1
Nickel	ppm	ASTM D5185m	>2	2	<1	1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	10	7	9
Lead	ppm	ASTM D5185m	>40	3	<1	2
Copper	ppm	ASTM D5185m	>330	12	10	13
Tin	ppm	ASTM D5185m	>15	2	0	1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	10	8	7
Potassium	ppm	ASTM D5185m	>20	4	5	5
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1.2	1	1.2
Nitration	Abs/cm	*ASTM D7624	>20	13.3	12.0	13.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	26.5	24.2	27.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>216	4	2	<1
Boron	ppm	ASTM D5185m	250	<1	0	0
Barium	ppm	ASTM D5185m	10	0	2	0
Molybdenum	ppm	ASTM D5185m	100	62	72	73
Manganese	ppm	ASTM D5185m		1	0	1
Magnesium	ppm	ASTM D5185m	450	923	1081	1092
Calcium	ppm	ASTM D5185m	3000	1059	1189	1211
Phosphorus	ppm	ASTM D5185m	1150	1013	1060	1160
Zinc	ppm	ASTM D5185m	1350	1253	1368	1442
Sulfur	ppm	ASTM D5185m	4250	2632	2943	2741
Oxidation	Abs/.1mm	*ASTM D7414	>25	24.0	20.5	26.0
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	3.6	5.5	4.2
Visc @ 100°C	cSt	ASTM D445	14.4	12.6	13.3	13.5


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : NL0002291

Lab Number : 06187017

Unique Number : 11043769

Test Package : FLEET

Received : 21 May 2024

Tested : 23 May 2024

Diagnosed : 23 May 2024 - Wes Davis

KIRK NATIONALEASE - SHOP 49

601 England Rd.

Lincoln, AL

US 35096

Contact: Skip Womack

shop49@knl.cc

T: (205)548-3004

F: (205)548-3006

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)