



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
3627C AUTOCAR ACX

Component
Natural Gas Engine

Fluid
PETRO CANADA DURON GEO LD 15W40 (48 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0103185	GFL0094661	GFL0094705
Sample Date		Client Info		17 May 2024	06 Nov 2023	19 Oct 2023
Machine Age	hrs	Client Info		2919	2119	23765
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	24	19	19
Chromium	ppm	ASTM D5185m	>4	3	2	2
Nickel	ppm	ASTM D5185m	>2	0	<1	<1
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	5	3	4
Lead	ppm	ASTM D5185m	>30	4	3	3
Copper	ppm	ASTM D5185m	>35	2	5	4
Tin	ppm	ASTM D5185m	>4	2	<1	1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>+100	15	12	14
Potassium	ppm	ASTM D5185m	>20	<1	7	7
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	8.1	11.0	9.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.8	22.8	21.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	16	19
Boron	ppm	ASTM D5185m	50	39	8	13
Barium	ppm	ASTM D5185m	5	0	5	0
Molybdenum	ppm	ASTM D5185m	50	91	53	52
Manganese	ppm	ASTM D5185m	0	3	<1	1
Magnesium	ppm	ASTM D5185m	560	685	519	539
Calcium	ppm	ASTM D5185m	1510	1374	1540	1546
Phosphorus	ppm	ASTM D5185m	780	774	721	684
Zinc	ppm	ASTM D5185m	870	918	921	947
Sulfur	ppm	ASTM D5185m	2040	2866	2531	2312
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.5	19.9	18.7
Base Number (BN)	mg KOH/g	ASTM D2896	10.2	5.8	4.4	4.9
Visc @ 100°C	cSt	ASTM D445	15.1	14.2	15.1	15.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0103185
Lab Number : 06187031
Unique Number : 11043783
Test Package : FLEET
Received : 21 May 2024
Tested : 23 May 2024
Diagnosed : 23 May 2024 - Wes Davis

GFL Environmental - 001 - Raleigh(CNG)

3741 Conquest Drive
 Garner, NC
 US 27529

Contact: Craig Johnson
 craig.johnson@gflenv.com

T: (919)662-7100
 F: (919)662-7130

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)