



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |



Area
MONTGOMERY
Machine Id
MACK 920015-192536
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | GFL0088007 | GFL0088014 | GFL0083557 |
| Sample Date | | Client Info | | 21 May 2024 | 08 May 2024 | 04 Apr 2024 |
| Machine Age | hrs | Client Info | | 13483 | 8456 | 13110 |
| Oil Age | hrs | Client Info | | 1134 | 0 | 761 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | Changed | Not Changd | Not Changd |
| Filter Changed | | Client Info | | Changed | Not Changd | Not Changd |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >120 | 13 | 14 | 3 |
| Chromium | ppm | ASTM D5185m | >20 | 0 | <1 | 0 |
| Nickel | ppm | ASTM D5185m | >5 | 0 | <1 | 0 |
| Titanium | ppm | ASTM D5185m | >2 | 0 | <1 | 0 |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >20 | 4 | 5 | 1 |
| Lead | ppm | ASTM D5185m | >40 | <1 | <1 | 0 |
| Copper | ppm | ASTM D5185m | >330 | <1 | 1 | 0 |
| Tin | ppm | ASTM D5185m | >15 | <1 | <1 | <1 |
| Vanadium | ppm | ASTM D5185m | | 0 | <1 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION








There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >25 | 8 | 10 | 3 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | 4 | 0 |
| Fuel | | WC Method | >3.0 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | *ASTM D7844 | >4 | 0.4 | 0.4 | 0.2 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 7.3 | 7.6 | 6.3 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 19.0 | 19.4 | 18.5 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|--------------|------|------|
| Sodium | ppm | ASTM D5185m | | 4 | 6 | 2 |
| Boron | ppm | ASTM D5185m | 0 | 2 | 2 | 3 |
| Barium | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 60 | 63 | 77 | 58 |
| Manganese | ppm | ASTM D5185m | 0 | <1 | 0 | <1 |
| Magnesium | ppm | ASTM D5185m | 1010 | 965 | 1211 | 925 |
| Calcium | ppm | ASTM D5185m | 1070 | 1061 | 1331 | 1047 |
| Phosphorus | ppm | ASTM D5185m | 1150 | 1007 | 1281 | 978 |
| Zinc | ppm | ASTM D5185m | 1270 | 1239 | 1624 | 1169 |
| Sulfur | ppm | ASTM D5185m | 2060 | 3057 | 3752 | 3082 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 14.8 | 15.0 | 14.2 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 9.8 | 7.2 | 7.3 | 8.0 |
| Visc @ 100°C | cSt | ASTM D445 | 15.4 | 13.9 | 13.7 | 13.8 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0088007
Lab Number : 06187181
Unique Number : 11043933
Test Package : FLEET

Received : 21 May 2024
Tested : 23 May 2024
Diagnosed : 23 May 2024 - Wes Davis

GFL Environmental - 955 - Montgomery
 1121 Wilbanks St
 Montgomery, AL
 US 36108
 Contact: LISA REEVES

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: