



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**(EFZ561)**  
Machine Id  
**817000**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (32 QTS)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0111412</b>	GFL0068816	GFL0097150
Sample Date		Client Info		<b>20 May 2024</b>	22 Mar 2024	05 Dec 2023
Machine Age	hrs	Client Info		<b>15635</b>	15360	14946
Oil Age	hrs	Client Info		<b>689</b>	414	594
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Changd
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>8</b>	9	10
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	<1	0
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	1	<1
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	3	4
Lead	ppm	ASTM D5185m	>40	<b>1</b>	2	2
Copper	ppm	ASTM D5185m	>330	<b>2</b>	2	2
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>5</b>	9	10
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	3	<1
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.3</b>	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.8</b>	7.6	8.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.6</b>	19.0	20.0
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	<1	5
Boron	ppm	ASTM D5185m	0	<b>4</b>	4	4
Barium	ppm	ASTM D5185m	0	<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185m	60	<b>63</b>	59	55
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>1007</b>	903	875
Calcium	ppm	ASTM D5185m	1070	<b>1159</b>	1060	973
Phosphorus	ppm	ASTM D5185m	1150	<b>1031</b>	1039	932
Zinc	ppm	ASTM D5185m	1270	<b>1327</b>	1166	1184
Sulfur	ppm	ASTM D5185m	2060	<b>3235</b>	2813	2522
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.7</b>	15.2	16.4
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>6.6</b>	7.1	6.4
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.3</b>	13.0	13.0



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0111412  
**Lab Number** : 06187494  
**Unique Number** : 11044246  
**Test Package** : FLEET

**Received** : 22 May 2024  
**Tested** : 23 May 2024  
**Diagnosed** : 23 May 2024 - Wes Davis

GFL Environmental - 073 - Warner Robins - Transwaste  
 155 Story Road  
 Warner Robins, GA  
 US 31093  
 Contact: JOSH MALONEY  
 jmaloney@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: