



# OIL ANALYSIS REPORT

|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |

Machine Id  
**SZLG530412**  
 Component  
**Diesel Engine**  
 Fluid  
**{not provided} (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|----------|
| Sample Number  |     | Client Info |           | <b>WC0911065</b>   | WC0614851   | ---      |
| Sample Date    |     | Client Info |           | <b>09 Apr 2024</b> | 10 Sep 2021 | ---      |
| Machine Age    | hrs | Client Info |           | <b>6293</b>        | 3118        | ---      |
| Oil Age        | hrs | Client Info |           | <b>0</b>           | 0           | ---      |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | 0           | ---      |
| Oil Changed    |     | Client Info |           | <b>N/A</b>         | Changed     | ---      |
| Filter Changed |     | Client Info |           | <b>N/A</b>         | Changed     | ---      |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | ---      |

## WEAR

All component wear rates are normal.

|              |        |             |      |              |      |     |
|--------------|--------|-------------|------|--------------|------|-----|
| Iron         | ppm    | ASTM D5185m | >100 | <b>12</b>    | 11   | --- |
| Chromium     | ppm    | ASTM D5185m | >20  | <b>&lt;1</b> | 0    | --- |
| Nickel       | ppm    | ASTM D5185m | >4   | <b>0</b>     | 0    | --- |
| Titanium     | ppm    | ASTM D5185m |      | <b>0</b>     | 0    | --- |
| Silver       | ppm    | ASTM D5185m | >3   | <b>&lt;1</b> | 0    | --- |
| Aluminum     | ppm    | ASTM D5185m | >20  | <b>3</b>     | 3    | --- |
| Lead         | ppm    | ASTM D5185m | >40  | <b>0</b>     | 0    | --- |
| Copper       | ppm    | ASTM D5185m | >330 | <b>4</b>     | 3    | --- |
| Tin          | ppm    | ASTM D5185m | >15  | <b>&lt;1</b> | 0    | --- |
| Vanadium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | 0    | --- |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | --- |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | --- |

## CONTAMINATION








There is no indication of any contamination in the oil.

|                  |          |             |       |                |       |     |
|------------------|----------|-------------|-------|----------------|-------|-----|
| Silicon          | ppm      | ASTM D5185m | >25   | <b>12</b>      | 20    | --- |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>0</b>       | <1    | --- |
| Fuel             |          | WC Method   | >5    | <b>&lt;1.0</b> | <1.0  | --- |
| Water            |          | WC Method   | >0.2  | <b>NEG</b>     | NEG   | --- |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | --- |
| Soot %           | %        | *ASTM D7844 | >3    | <b>0.1</b>     | 0.1   | --- |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>8.9</b>     | 12    | --- |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>21.6</b>    | 24.2  | --- |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | --- |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | --- |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | --- |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | --- |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | --- |
| Emulsified Water | scalar   | *Visual     | >0.2  | <b>NEG</b>     | NEG   | --- |

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

|                  |          |             |     |              |      |     |
|------------------|----------|-------------|-----|--------------|------|-----|
| Sodium           | ppm      | ASTM D5185m |     | <b>12</b>    | 9    | --- |
| Boron            | ppm      | ASTM D5185m |     | <b>216</b>   | 179  | --- |
| Barium           | ppm      | ASTM D5185m |     | <b>0</b>     | 0    | --- |
| Molybdenum       | ppm      | ASTM D5185m |     | <b>93</b>    | 131  | --- |
| Manganese        | ppm      | ASTM D5185m |     | <b>&lt;1</b> | 0    | --- |
| Magnesium        | ppm      | ASTM D5185m |     | <b>544</b>   | 584  | --- |
| Calcium          | ppm      | ASTM D5185m |     | <b>1688</b>  | 1544 | --- |
| Phosphorus       | ppm      | ASTM D5185m |     | <b>1145</b>  | 736  | --- |
| Zinc             | ppm      | ASTM D5185m |     | <b>1443</b>  | 900  | --- |
| Sulfur           | ppm      | ASTM D5185m |     | <b>3840</b>  | 2121 | --- |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25 | <b>19.8</b>  | 27   | --- |
| Base Number (BN) | mg KOH/g | ASTM D2896  |     | <b>7.4</b>   | 5.7  | --- |
| Visc @ 100°C     | cSt      | ASTM D445   |     | <b>14.1</b>  | 14.4 | --- |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0911065  
**Lab Number** : 06188397  
**Unique Number** : 11045149  
**Test Package** : FLEET

**Received** : 22 May 2024  
**Tested** : 24 May 2024  
**Diagnosed** : 24 May 2024 - Wes Davis

**DOLE FRESH FRUIT**  
 PO BOX 725, ATTN: MAINTENANCE AND REPAIR  
 NEW CASTLE, DE  
 US 19720

Contact: LUIS LAPIERRE  
 luis.lapierre@dole.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (302)652-6344  
 F: (302)652-6061