



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**934057**  
 Component  
**Natural Gas Engine**  
 Fluid  
**PETRO CANADA DURON GEO LD 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0117809</b>	GFL0114474	GFL0114481
Sample Date		Client Info		<b>14 May 2024</b>	12 Mar 2024	04 Mar 2024
Machine Age	mls	Client Info		<b>35761</b>	27646	1772
Oil Age	mls	Client Info		<b>0</b>	0	0
Filter Age	mls	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Not Changd	Changed
Filter Changed		Client Info		<b>Changed</b>	Not Changd	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>50	<b>20</b>	7	23
Chromium	ppm	ASTM D5185m	>4	<b>2</b>	<1	2
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>9	<b>11</b>	2	12
Lead	ppm	ASTM D5185m	>30	<b>2</b>	0	1
Copper	ppm	ASTM D5185m	>35	<b>2</b>	<1	2
Tin	ppm	ASTM D5185m	>4	<b>1</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>+100	<b>8</b>	4	6
Potassium	ppm	ASTM D5185m	>20	<b>22</b>	4	34
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844		<b>0.1</b>	0	0
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.1</b>	7.1	11.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>23.5</b>	19.1	22.2
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>8</b>	5	7
Boron	ppm	ASTM D5185m	50	<b>6</b>	29	6
Barium	ppm	ASTM D5185m	5	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	50	<b>55</b>	48	55
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	1
Magnesium	ppm	ASTM D5185m	560	<b>584</b>	554	606
Calcium	ppm	ASTM D5185m	1510	<b>1637</b>	1548	1695
Phosphorus	ppm	ASTM D5185m	780	<b>749</b>	752	741
Zinc	ppm	ASTM D5185m	870	<b>1047</b>	901	1005
Sulfur	ppm	ASTM D5185m	2040	<b>2780</b>	2891	2871
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>19.3</b>	15.9	18.9
Base Number (BN)	mg KOH/g	ASTM D2896	10.2	<b>4.1</b>	8.0	4.0
Visc @ 100°C	cSt	ASTM D445	15.1	<b>15.0</b>	14.7	14.9


**FT-IR (Direct Trend)**




**Ferrous Alloys**




**Base Number**




**Non-ferrous Metals**




**Viscosity @ 100°C**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0117809  
**Lab Number** : 06188511  
**Unique Number** : 11045263  
**Test Package** : FLEET

**Received** : 22 May 2024  
**Tested** : 24 May 2024  
**Diagnosed** : 24 May 2024 - Wes Davis

**GFL Environmental - 865 - East Mount Hauling**  
 7213 East Mount Houston Road  
 Houston, TX  
 US 77050

Contact: Saul Castillo  
 saul.castillo@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: