



|                 |           |
|-----------------|-----------|
| WEAR            | NORMAL    |
| CONTAMINATION   | NORMAL    |
| FLUID CONDITION | ATTENTION |

Machine Id  
**61938**  
 Component  
**Diesel Engine**  
 Fluid  
**MOBIL DELVAC 1300 SUPER15W40 (--- QTS)**

### RECOMMENDATION

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>IL0025748</b>   | IL0029810   | IL0029850   |
| Sample Date    |     | Client Info |           | <b>28 Feb 2024</b> | 28 Jun 2023 | 07 Feb 2023 |
| Machine Age    | mls | Client Info |           | <b>0</b>           | 0           | 0           |
| Oil Age        | mls | Client Info |           | <b>0</b>           | 0           | 0           |
| Filter Age     | mls | Client Info |           | <b>0</b>           | 0           | 0           |
| Oil Changed    |     | Client Info |           | <b>N/A</b>         | Changed     | Changed     |
| Filter Changed |     | Client Info |           | <b>N/A</b>         | Changed     | Changed     |
| Sample Status  |     |             |           | <b>ATTENTION</b>   | ATTENTION   | MARGINAL    |

### WEAR

All component wear rates are normal.

|              |        |             |      |              |      |      |
|--------------|--------|-------------|------|--------------|------|------|
| Iron         | ppm    | ASTM D5185m | >100 | <b>6</b>     | 7    | 10   |
| Chromium     | ppm    | ASTM D5185m | >20  | <b>&lt;1</b> | <1   | <1   |
| Nickel       | ppm    | ASTM D5185m | >4   | <b>0</b>     | <1   | 0    |
| Titanium     | ppm    | ASTM D5185m |      | <b>0</b>     | 0    | 0    |
| Silver       | ppm    | ASTM D5185m | >3   | <b>&lt;1</b> | 0    | 0    |
| Aluminum     | ppm    | ASTM D5185m | >20  | <b>2</b>     | 2    | 2    |
| Lead         | ppm    | ASTM D5185m | >40  | <b>0</b>     | 0    | 0    |
| Copper       | ppm    | ASTM D5185m | >330 | <b>&lt;1</b> | <1   | <1   |
| Tin          | ppm    | ASTM D5185m | >15  | <b>&lt;1</b> | 0    | <1   |
| Vanadium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | 0    | 0    |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |

### CONTAMINATION








There is no indication of any contamination in the oil.

|                  |          |             |       |                |       |       |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon          | ppm      | ASTM D5185m | >25   | <b>5</b>       | 5     | 6     |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>0</b>       | 1     | 3     |
| Fuel             |          | WC Method   | >5    | <b>&lt;1.0</b> | <1.0  | ▲ 2.9 |
| Water            |          | WC Method   | >0.2  | <b>NEG</b>     | NEG   | NEG   |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | NEG   |
| Soot %           | %        | *ASTM D7844 | >3    | <b>0.2</b>     | 0.2   | 0.3   |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>8.4</b>     | 7.9   | 10.4  |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>21.6</b>    | 23.5  | 23.1  |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Emulsified Water | scalar   | *Visual     | >0.2  | <b>NEG</b>     | NEG   | NEG   |

### FLUID CONDITION

The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

|                  |          |             |     |               |        |        |
|------------------|----------|-------------|-----|---------------|--------|--------|
| Sodium           | ppm      | ASTM D5185m |     | <b>2</b>      | 0      | 0      |
| Boron            | ppm      | ASTM D5185m | 0   | <b>62</b>     | 41     | 32     |
| Barium           | ppm      | ASTM D5185m | 0   | <b>0</b>      | <1     | 0      |
| Molybdenum       | ppm      | ASTM D5185m | 0   | <b>71</b>     | 42     | 22     |
| Manganese        | ppm      | ASTM D5185m |     | <b>&lt;1</b>  | <1     | <1     |
| Magnesium        | ppm      | ASTM D5185m | 0   | <b>573</b>    | 502    | 525    |
| Calcium          | ppm      | ASTM D5185m |     | <b>1719</b>   | 1619   | 1238   |
| Phosphorus       | ppm      | ASTM D5185m |     | <b>800</b>    | 736    | 590    |
| Zinc             | ppm      | ASTM D5185m |     | <b>931</b>    | 898    | 731    |
| Sulfur           | ppm      | ASTM D5185m |     | <b>3072</b>   | 2486   | 2322   |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25 | <b>22.2</b>   | 24.4   | 23.1   |
| Base Number (BN) | mg KOH/g | ASTM D2896  | 9.4 | <b>8.1</b>    | 9.5    | 6.8    |
| Visc @ 100°C     | cSt      | ASTM D445   | 14  | ● <b>12.4</b> | ● 12.4 | ▲ 12.4 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : IL0025748

Lab Number : 06188800

Unique Number : 11045552

Test Package : FLEET

Received : 23 May 2024

Tested : 24 May 2024

Diagnosed : 28 May 2024 - Don Baldrige

RUSH TRUCK LEASING - SPRINGFIELD IDEALEASE

3441 GATLIN DR

SPRINGFIELD, IL

US 62707

Contact: TODD CRUMPLER

crumplerc@rushenterprises.com

T: (217)718-2341

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)