



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(BD56781)
Machine Id
714050
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0100994	GFL0101058	GFL0092786
Sample Date		Client Info		17 May 2024	21 Feb 2024	31 Oct 2023
Machine Age	hrs	Client Info		521	521	521
Oil Age	hrs	Client Info		521	521	521
Filter Age	hrs	Client Info		0	0	521
Oil Changed		Client Info		N/A	Not Changd	Changed
Filter Changed		Client Info		N/A	Not Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>90	7	31	8
Chromium	ppm	ASTM D5185m	>20	0	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m	>2	0	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>20	2	4	2
Lead	ppm	ASTM D5185m	>40	0	0	<1
Copper	ppm	ASTM D5185m	>330	0	2	2
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	4	5	6
Potassium	ppm	ASTM D5185m	>20	<1	4	2
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	0.4	0.5	0.1
Nitration	Abs/cm	*ASTM D7624	>20	8.1	9.4	4.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.8	20.2	17.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		1	6	0
Boron	ppm	ASTM D5185m	0	12	6	12
Barium	ppm	ASTM D5185m	0	0	<1	7
Molybdenum	ppm	ASTM D5185m	60	60	65	64
Manganese	ppm	ASTM D5185m	0	<1	1	<1
Magnesium	ppm	ASTM D5185m	1010	886	878	843
Calcium	ppm	ASTM D5185m	1070	1001	1041	1001
Phosphorus	ppm	ASTM D5185m	1150	956	946	956
Zinc	ppm	ASTM D5185m	1270	1180	1114	1089
Sulfur	ppm	ASTM D5185m	2060	3344	2653	3483
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.2	17.1	13.0
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.8	7.2	8.9
Visc @ 100°C	cSt	ASTM D445	15.4	13.5	13.2	14.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : GFL0100994

Lab Number : 06188929

Unique Number : 11045681

Test Package : FLEET

Received : 23 May 2024

Tested : 24 May 2024

Diagnosed : 24 May 2024 - Wes Davis

GFL Environmental - 455 - Flint

2051 W. Bristol Rd

Flint Township, MI

US 48507

Contact: MARK WOMBLE

mwomble@gflenv.com

T: (586)825-9514

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)