



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**JOHN DEERE 650K 1T0650KKPNF414116**  
 Component  
**Right Final Drive**  
 Fluid  
**JOHN DEERE HY-GARD HYD/TRANS (--- GAL)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>JR0212767</b>	JR0184628	---
Sample Date		Client Info		<b>21 May 2024</b>	11 Jan 2024	---
Machine Age	hrs	Client Info		<b>990</b>	427	---
Oil Age	hrs	Client Info		<b>990</b>	427	---
Filter Age	hrs	Client Info		<b>0</b>	0	---
Oil Changed		Client Info		<b>Changed</b>	Not Changd	---
Filter Changed		Client Info		<b>None</b>	N/A	---
Sample Status				<b>NORMAL</b>	NORMAL	---

### WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	<b>43</b>	35	---
Iron	ppm	ASTM D5185m	>750	<b>57</b>	38	---
Chromium	ppm	ASTM D5185m	>9	<b>2</b>	<1	---
Nickel	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	---
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	---
Silver	ppm	ASTM D5185m		<b>&lt;1</b>	0	---
Aluminum	ppm	ASTM D5185m	>40	<b>2</b>	1	---
Lead	ppm	ASTM D5185m	>15	<b>&lt;1</b>	0	---
Copper	ppm	ASTM D5185m	>40	<b>6</b>	<1	---
Tin	ppm	ASTM D5185m	>10	<b>1</b>	0	---
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---

### CONTAMINATION






There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	<b>7</b>	6	---
Potassium	ppm	ASTM D5185m	>20	<b>9</b>	6	---
Water		WC Method	>0.075	<b>NEG</b>	NEG	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Emulsified Water	scalar	*Visual	>0.075	<b>NEG</b>	NEG	---

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	<b>1</b>	3	---
Boron	ppm	ASTM D5185m	6	<b>3</b>	2	---
Barium	ppm	ASTM D5185m	0	<b>&lt;1</b>	1	---
Molybdenum	ppm	ASTM D5185m	0	<b>&lt;1</b>	2	---
Manganese	ppm	ASTM D5185m		<b>6</b>	2	---
Magnesium	ppm	ASTM D5185m	145	<b>107</b>	105	---
Calcium	ppm	ASTM D5185m	3570	<b>3709</b>	3422	---
Phosphorus	ppm	ASTM D5185m	1290	<b>1058</b>	1047	---
Zinc	ppm	ASTM D5185m	1640	<b>1393</b>	1251	---
Sulfur	ppm	ASTM D5185m		<b>4130</b>	3930	---
Visc @ 40°C	cSt	ASTM D445	57.0	<b>51.9</b>	54.3	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : JR0212767

**Lab Number** : 06189523

**Unique Number** : 11046275

**Test Package** : CONST ( Additional Tests: PQ )

**Received** : 23 May 2024

**Tested** : 24 May 2024

**Diagnosed** : 24 May 2024 - Wes Davis

**JRE - STEPHENSON**

245 YARDMASTER COURT

STEPHENSON, VA

US 22656-1761

Contact: PHIL DAUGHERTY

pdaugherty@jamesriverequipment.com

T: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (540)693-2588