



VOLVO PENTA

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
CRAIG MALY [MATTHEW DOW]
Machine Id
VOLVO PENTA 3940017594
Component
Port IPS
Fluid
GEAR OIL SAE 75W90 (4 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VPA050872	VPA055920	VPA035285
Sample Date		Client Info		05 Apr 2024	14 Apr 2023	09 Mar 2022
Machine Age	hrs	Client Info		282	260	243
Oil Age	hrs	Client Info		39	17	22
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Changed
Filter Changed		Client Info		Changed	Not Changd	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		13	15	12
Iron	ppm	ASTM D5185m	>200	6	4	5
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		<1	0	0
Aluminum	ppm	ASTM D5185m		2	0	<1
Lead	ppm	ASTM D5185m		<1	0	0
Copper	ppm	ASTM D5185m		3	<1	1
Tin	ppm	ASTM D5185m		1	0	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m		7	6	5
Potassium	ppm	ASTM D5185m	>20	1	<1	0
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		0	0	<1
Boron	ppm	ASTM D5185m	400	373	353	359
Barium	ppm	ASTM D5185m	200	0	0	0
Molybdenum	ppm	ASTM D5185m	12	<1	0	0
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m	12	2	<1	0
Calcium	ppm	ASTM D5185m	150	11	11	2
Phosphorus	ppm	ASTM D5185m	1650	1242	1265	1314
Zinc	ppm	ASTM D5185m	125	7	6	<1
Sulfur	ppm	ASTM D5185m	22500	25079	26056	19350
Visc @ 40°C	cSt	ASTM D445	109	107	106	108



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VPA050872 **Received** : 23 May 2024
Lab Number : 06189541 **Tested** : 24 May 2024
Unique Number : 11046293 **Diagnosed** : 28 May 2024 - Don Baldrige
Test Package : MOB 1 (Additional Tests: PQ)

Mobile Marine Services Inc
 01032 Advance Rd South
 EAST JORDAN, MI
 US 49727
 Contact: Duane Kujat
 mobilemarine@twin-valley.net
 T: Phone
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)