



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**728080**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0097848</b>	GFL0103606	GFL0085303
Sample Date		Client Info		<b>17 May 2024</b>	08 Jan 2024	09 Oct 2023
Machine Age	hrs	Client Info		<b>10887</b>	10887	10887
Oil Age	hrs	Client Info		<b>600</b>	500	600
Filter Age	hrs	Client Info		<b>600</b>	500	600
Oil Changed		Client Info		<b>N/A</b>	N/A	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	<b>23</b>	18	24
Chromium	ppm	ASTM D5185m	>5	<b>1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>30	<b>3</b>	2	4
Lead	ppm	ASTM D5185m	>30	<b>&lt;1</b>	0	0
Copper	ppm	ASTM D5185m	>150	<b>2</b>	2	2
Tin	ppm	ASTM D5185m	>5	<b>1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>20	<b>7</b>	6	6
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	4	10
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.5</b>	0.4	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.4</b>	10.5	10.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.2</b>	22.1	22.2
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>5</b>	0	7
Boron	ppm	ASTM D5185m	0	<b>0</b>	<1	<1
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	12
Molybdenum	ppm	ASTM D5185m	60	<b>65</b>	55	57
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>1011</b>	871	933
Calcium	ppm	ASTM D5185m	1070	<b>1147</b>	953	1001
Phosphorus	ppm	ASTM D5185m	1150	<b>1008</b>	947	912
Zinc	ppm	ASTM D5185m	1270	<b>1321</b>	1118	1179
Sulfur	ppm	ASTM D5185m	2060	<b>3300</b>	2987	2833
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.7</b>	21.7	21.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.2</b>	6.4	5.8
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	13.5	14.0


**FT-IR (Direct Trend)**




**Ferrous Alloys**




**Base Number**




**Non-ferrous Metals**




**Viscosity @ 100°C**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0097848  
**Lab Number** : 06189976  
**Unique Number** : 11046728  
**Test Package** : FLEET

**Received** : 23 May 2024  
**Tested** : 25 May 2024  
**Diagnosed** : 25 May 2024 - Wes Davis

**GFL Environmental - 958 - Tri County HC Morton**  
 1090 W. Jefferson St.  
 Morton, IL  
 US 61550  
 Contact: Bryan Link  
 blink@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: