



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(BD70667)
Machine Id
814029 MACK LR64R
Component
Diesel Engine
Fluid
TIER ONE 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0115236	GFL0115298	GFL0102231
Sample Date		Client Info		20 May 2024	01 May 2024	03 Apr 2024
Machine Age	hrs	Client Info		1343	1201	1044
Oil Age	hrs	Client Info		13	23	2
Filter Age	hrs	Client Info		13	23	2
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	Changed	Changed
Sample Status				NORMAL	NORMAL	ATTENTION

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	36	6	20
Chromium	ppm	ASTM D5185m	>20	1	<1	<1
Nickel	ppm	ASTM D5185m	>5	<1	1	4
Titanium	ppm	ASTM D5185m	>2	<1	1	0
Silver	ppm	ASTM D5185m	>2	1	<1	<1
Aluminum	ppm	ASTM D5185m	>20	7	2	<1
Lead	ppm	ASTM D5185m	>40	<1	3	2
Copper	ppm	ASTM D5185m	>330	3	17	220
Tin	ppm	ASTM D5185m	>15	1	2	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	9	4	10
Potassium	ppm	ASTM D5185m	>20	10	3	<1
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>4	0.5	0.2	0.6
Nitration	Abs/cm	*ASTM D7624	>20	8.5	6.4	8.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.4	18.3	20.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		9	4	3
Boron	ppm	ASTM D5185m		4	6	14
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		28	51	60
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m		284	944	895
Calcium	ppm	ASTM D5185m		1559	1168	1164
Phosphorus	ppm	ASTM D5185m		738	1128	987
Zinc	ppm	ASTM D5185m		1010	1304	1174
Sulfur	ppm	ASTM D5185m		2761	3999	3033
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.5	13.6	17.5
Base Number (BN)	mg KOH/g	ASTM D2896		7.3	8.4	7.2
Visc @ 100°C	cSt	ASTM D445		13.1	12.9	13.0



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0115236
Lab Number : 06189985
Unique Number : 11046737
Test Package : FLEET

GFL Environmental - 642- Grand Rapids Hauling
 5826 Alden Nash Ave SE
 Lowell, MI
 US 49331
 Contact: Chad Crosby
 ccrosby@gflenv.com
 T: (616)299-8425
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)