



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
834022
Component
Natural Gas Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0122653	GFL0114501	GFL0074623
Sample Date		Client Info		22 May 2024	18 Apr 2024	20 Dec 2023
Machine Age	hrs	Client Info		2049	1801	1173
Oil Age	hrs	Client Info		867	0	0
Filter Age	hrs	Client Info		867	0	0
Oil Changed		Client Info		Changed	N/A	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	33	32	59
Chromium	ppm	ASTM D5185m	>5	2	1	2
Nickel	ppm	ASTM D5185m	>4	2	0	1
Titanium	ppm	ASTM D5185m	>5	<1	0	0
Silver	ppm	ASTM D5185m	>3	1	0	0
Aluminum	ppm	ASTM D5185m	>25	9	8	26
Lead	ppm	ASTM D5185m	>40	2	1	<1
Copper	ppm	ASTM D5185m	>150	5	4	15
Tin	ppm	ASTM D5185m	>4	2	1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	9	7	25
Potassium	ppm	ASTM D5185m	>20	20	16	75
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.3	0	0
Nitration	Abs/cm	*ASTM D7624	>20	10.5	9.2	12.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.9	20.9	25.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		4	2	6
Boron	ppm	ASTM D5185m	0	14	0	2
Barium	ppm	ASTM D5185m	0	0	<1	2
Molybdenum	ppm	ASTM D5185m	60	78	72	54
Manganese	ppm	ASTM D5185m	0	3	3	12
Magnesium	ppm	ASTM D5185m	1010	973	952	833
Calcium	ppm	ASTM D5185m	1070	1271	1226	1257
Phosphorus	ppm	ASTM D5185m	1150	936	991	710
Zinc	ppm	ASTM D5185m	1270	1320	1208	954
Sulfur	ppm	ASTM D5185m	2060	2954	3172	2100
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.0	15.6	22.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.9	4.4	2.9
Visc @ 100°C	cSt	ASTM D445	15.4	13.1	13.3	13.8



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0122653
Lab Number : 06190063
Unique Number : 11046815
Test Package : FLEET

Received : 23 May 2024
Tested : 25 May 2024
Diagnosed : 29 May 2024 - Don Baldrige

GFL Environmental - 095 - Atlanta West
 2699 Cochran Industrial Blvd
 Douglasville, GA
 US 30127-1332

Contact: Darrell Welch
 darrell.welch@gflenv.com

T: (800)207-6618
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)