



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Area
(BC71121)
Machine Id
4593M
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (5 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | GFL0115134 | GFL0115121 | GFL0106709 |
| Sample Date | | Client Info | | 19 May 2024 | 12 Mar 2024 | 20 Feb 2024 |
| Machine Age | hrs | Client Info | | 7472 | 7253 | 7188 |
| Oil Age | hrs | Client Info | | 284 | 65 | 600 |
| Filter Age | hrs | Client Info | | 284 | 65 | 600 |
| Oil Changed | | Client Info | | Changed | Not Changd | Changed |
| Filter Changed | | Client Info | | Changed | Not Changed | Changed |
| Sample Status | | | | NORMAL | ABNORMAL | ABNORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >100 | 40 | 17 | 62 |
| Chromium | ppm | ASTM D5185m | >20 | <1 | <1 | 3 |
| Nickel | ppm | ASTM D5185m | >4 | <1 | <1 | 1 |
| Titanium | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Silver | ppm | ASTM D5185m | >3 | <1 | <1 | 0 |
| Aluminum | ppm | ASTM D5185m | >20 | 4 | 3 | 6 |
| Lead | ppm | ASTM D5185m | >40 | <1 | <1 | <1 |
| Copper | ppm | ASTM D5185m | >330 | 2 | 8 | 20 |
| Tin | ppm | ASTM D5185m | >15 | <1 | <1 | 0 |
| Vanadium | ppm | ASTM D5185m | | <1 | <1 | <1 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION








There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >25 | 10 | 11 | ▲ 43 |
| Potassium | ppm | ASTM D5185m | >20 | 6 | 5 | ▲ 17 |
| Fuel | | WC Method | >5 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | *ASTM D7844 | >3 | 0.5 | 0.2 | 0.5 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 6.6 | 8.1 | 18.4 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 19.1 | 19.0 | 26.1 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|--------------|-------|--------|
| Sodium | ppm | ASTM D5185m | | 65 | ▲ 377 | ▲ 2025 |
| Boron | ppm | ASTM D5185m | 0 | 5 | 15 | 62 |
| Barium | ppm | ASTM D5185m | 0 | 0 | 2 | 0 |
| Molybdenum | ppm | ASTM D5185m | 60 | 57 | 72 | 136 |
| Manganese | ppm | ASTM D5185m | 0 | <1 | <1 | 1 |
| Magnesium | ppm | ASTM D5185m | 1010 | 983 | 942 | 1076 |
| Calcium | ppm | ASTM D5185m | 1070 | 1063 | 1126 | 1259 |
| Phosphorus | ppm | ASTM D5185m | 1150 | 1022 | 1063 | 1093 |
| Zinc | ppm | ASTM D5185m | 1270 | 1297 | 1241 | 1385 |
| Sulfur | ppm | ASTM D5185m | 2060 | 3508 | 3431 | 3117 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 14.3 | 15.4 | 21.0 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 9.8 | 9.1 | 9.8 | 11.6 |
| Visc @ 100°C | cSt | ASTM D445 | 15.4 | 14.6 | 13.9 | 15.6 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0115134
Lab Number : 06190223
Unique Number : 11046975
Test Package : FLEET

Received : 24 May 2024
Tested : 28 May 2024
Diagnosed : 28 May 2024 - Wes Davis

GFL Environmental - 405 - Arbor Hills
 7811 Chubb Rd
 NORTHVILLE, MI
 US 48168

Contact: Anthony Hopkins
 ahopkins@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: