



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 350G 1FF350GXTMF815037
 Component
Right Final Drive
 Fluid
JOHN DEERE GL-5 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0214878	JR0198478	JR0171831
Sample Date		Client Info		22 May 2024	08 Jan 2024	08 Jun 2023
Machine Age	hrs	Client Info		4428	4428	3484
Oil Age	hrs	Client Info		4428	3928	1500
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Changed	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	SEVERE	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	87	301	13
Iron	ppm	ASTM D5185m	>750	257	▲ 1205	3
Chromium	ppm	ASTM D5185m	>9	3	10	0
Nickel	ppm	ASTM D5185m	>10	1	<1	0
Titanium	ppm	ASTM D5185m		2	5	<1
Silver	ppm	ASTM D5185m		1	0	0
Aluminum	ppm	ASTM D5185m	>40	22	● 128	<1
Lead	ppm	ASTM D5185m	>15	<1	0	0
Copper	ppm	ASTM D5185m	>40	2	2	0
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	51	▲ 278	1
Potassium	ppm	ASTM D5185m	>20	5	18	0
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	<1	8	<1
Boron	ppm	ASTM D5185m		19	153	61
Barium	ppm	ASTM D5185m		1	<1	0
Molybdenum	ppm	ASTM D5185m		1	0	0
Manganese	ppm	ASTM D5185m		3	12	0
Magnesium	ppm	ASTM D5185m		4	8	0
Calcium	ppm	ASTM D5185m		6	13	16
Phosphorus	ppm	ASTM D5185m		401	942	709
Zinc	ppm	ASTM D5185m		9	10	0
Sulfur	ppm	ASTM D5185m		19127	18705	23059
Visc @ 40°C	cSt	ASTM D445		140	152	140



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0214878 **Received** : 24 May 2024
Lab Number : 06190740 **Tested** : 29 May 2024
Unique Number : 11047492 **Diagnosed** : 29 May 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com
 T: (704)597-0211
 F: (704)596-6198

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)