



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

[16W16293]

Machine Id

JOHN DEERE 544 P 1DW544PAHNLZ15954

Component

Rear Axle

Fluid

JOHN DEERE HY-GARD HYD/TRANS (18 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: 16W16293)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0207189	JR0196354	JR0185343
Sample Date		Client Info		22 May 2024	15 Feb 2024	26 Sep 2023
Machine Age	hrs	Client Info		1476	982	472
Oil Age	hrs	Client Info		1004	510	472
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		47	47	126
Iron	ppm	ASTM D5185m	>750	72	108	220
Chromium	ppm	ASTM D5185m	>11	1	<1	2
Nickel	ppm	ASTM D5185m	>10	<1	0	2
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		1	0	0
Aluminum	ppm	ASTM D5185m	>21	1	5	4
Lead	ppm	ASTM D5185m	>49	4	2	12
Copper	ppm	ASTM D5185m	>101	6	3	18
Tin	ppm	ASTM D5185m	>10	1	<1	1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	MODER	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>31	11	▲ 43	24
Potassium	ppm	ASTM D5185m	>20	2	0	3
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	0	2	5
Boron	ppm	ASTM D5185m	6	3	<1	2
Barium	ppm	ASTM D5185m	0	1	0	6
Molybdenum	ppm	ASTM D5185m	0	1	<1	<1
Manganese	ppm	ASTM D5185m		3	3	11
Magnesium	ppm	ASTM D5185m	145	103	96	93
Calcium	ppm	ASTM D5185m	3570	3517	3309	3390
Phosphorus	ppm	ASTM D5185m	1290	1016	1016	1023
Zinc	ppm	ASTM D5185m	1640	1273	1197	1234
Sulfur	ppm	ASTM D5185m		4433	5002	4208
Visc @ 40°C	cSt	ASTM D445	57.0	53.3	54.9	54.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0207189 **Received** : 24 May 2024
Lab Number : 06190746 **Tested** : 29 May 2024
Unique Number : 11047498 **Diagnosed** : 29 May 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

JRE - CASTLE HAYNE
 113 CROWATAN ROAD
 CASTLE HAYNE, NC
 US 28429-5819

Contact: WILMINGTON SHOP

todd.simmons@jamesriverequipment.com; canastasio@wearcheck.com; canastasio@we

T: (910)675-9211

F: