



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
KOMATSU PC-490 TH-12 (S/N A41656)
Component
Diesel Engine
Fluid
DIESEL ENGINE OIL SAE 40 (12 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		CL0005448	CL0005151	CL0004708
Sample Date		Client Info		20 May 2024	09 Feb 2024	14 Sep 2023
Machine Age	hrs	Client Info		5857	5595	5325
Oil Age	hrs	Client Info		262	270	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	8	12	16
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	<1	0	0
Aluminum	ppm	ASTM D5185m	>20	2	2	2
Lead	ppm	ASTM D5185m	>40	8	4	6
Copper	ppm	ASTM D5185m	>330	3	3	5
Tin	ppm	ASTM D5185m	>15	<1	1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	6	5	8
Potassium	ppm	ASTM D5185m	>20	2	<1	<1
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	0.4	0.5
Nitration	Abs/cm	*ASTM D7624	>20	11.0	11.7	12.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.0	22.5	23.2
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>216	2	1	4
Boron	ppm	ASTM D5185m	250	22	27	29
Barium	ppm	ASTM D5185m	10	0	0	1
Molybdenum	ppm	ASTM D5185m	100	85	80	101
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	450	502	122	140
Calcium	ppm	ASTM D5185m	3000	2071	2273	2530
Phosphorus	ppm	ASTM D5185m	1150	1220	1120	1203
Zinc	ppm	ASTM D5185m	1350	1441	1363	1430
Sulfur	ppm	ASTM D5185m	4250	4416	3859	4719
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.8	19.4	20.1
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	7.8	6.3	6.3
Visc @ 100°C	cSt	ASTM D445	14.4	14.1	13.6	13.9


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : CL0005448
Lab Number : 06191475
Unique Number : 11048227
Test Package : CONST (Additional Tests: TBN)

Received : 24 May 2024
Tested : 29 May 2024
Diagnosed : 29 May 2024 - Wes Davis

BULLSEYE CONSTRUCTION
 581 N POLK ST
 PINEVILLE, NC
 US 28134
 Contact: SERVICE MANAGER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: