



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**FRANK JOHNSON**  
Machine Id  
**[FRANK JOHNSON] 008 298198-8**  
Component  
**Starboard Genset**  
Fluid  
**CHEVRON DELO 400 XLE 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0065686</b>	MW0068013	MW0066216
Sample Date		Client Info		<b>11 May 2024</b>	16 Apr 2024	29 Mar 2024
Machine Age	hrs	Client Info		<b>2531</b>	2277	2027
Oil Age	hrs	Client Info		<b>254</b>	248	184
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	N/A	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	<b>6</b>	7	4
Chromium	ppm	ASTM D5185m	>4	<b>0</b>	0	<1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m		<b>9</b>	<1	2
Silver	ppm	ASTM D5185m	>5	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>12	<b>2</b>	2	2
Lead	ppm	ASTM D5185m	>17	<b>0</b>	0	<1
Copper	ppm	ASTM D5185m	>70	<b>1</b>	3	<1
Tin	ppm	ASTM D5185m	>15	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	<b>5</b>	5	4
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	0	20
Fuel		WC Method	>4.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844		<b>0.5</b>	0.4	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>8.4</b>	7.0	6.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>20.3</b>	23.0	22.5
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>2</b>	1	4
Boron	ppm	ASTM D5185m		<b>152</b>	260	291
Barium	ppm	ASTM D5185m		<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>72</b>	126	109
Manganese	ppm	ASTM D5185m		<b>2</b>	2	1
Magnesium	ppm	ASTM D5185m		<b>739</b>	687	605
Calcium	ppm	ASTM D5185m		<b>1574</b>	1787	1671
Phosphorus	ppm	ASTM D5185m	760	<b>742</b>	770	724
Zinc	ppm	ASTM D5185m	830	<b>832</b>	884	807
Sulfur	ppm	ASTM D5185m	2770	<b>3364</b>	3389	3069
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.4</b>	16.3	15.8
Base Number (BN)	mg KOH/g	ASTM D2896	10.7	<b>7.3</b>	8.6	8.5
Visc @ 100°C	cSt	ASTM D445	14.9	<b>13.7</b>	13.3	13.5


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : MW0065686

**Lab Number** : 06191620

**Unique Number** : 11048372

**Test Package** : MAR 2

**Received** : 24 May 2024

**Tested** : 29 May 2024

**Diagnosed** : 29 May 2024 - Wes Davis

**INGRAM BARGE**

900 S 3RD ST

PADUCAH, KY

US 42003

Contact: GLENN ELLIS

glen.ellis@ingrambarga.com

T: (270)415-4467

F: (615)695-3697

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)