



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**727068-361321**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0118243</b>	GFL0118182	GFL0109192
Sample Date		Client Info		<b>16 May 2024</b>	25 Apr 2024	30 Mar 2024
Machine Age	hrs	Client Info		<b>4982</b>	12422	4655
Oil Age	hrs	Client Info		<b>700</b>	300	700
Filter Age	hrs	Client Info		<b>700</b>	0	700
Oil Changed		Client Info		<b>Changed</b>	N/A	Changed
Filter Changed		Client Info		<b>Changed</b>	Not Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	ABNORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>41</b>	13	49
Chromium	ppm	ASTM D5185m	>20	<b>2</b>	<1	<1
Nickel	ppm	ASTM D5185m	>5	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>1</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	<1	2
Lead	ppm	ASTM D5185m	>40	<b>3</b>	<1	2
Copper	ppm	ASTM D5185m	>330	<b>7</b>	3	0
Tin	ppm	ASTM D5185m	>15	<b>1</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>5</b>	2	3
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	<1	2
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>3.4</b>	2.1	▲ 5.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.3</b>	6.6	11.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>23.5</b>	20.7	27.6
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>4</b>	1	2
Boron	ppm	ASTM D5185m	0	<b>&lt;1</b>	1	1
Barium	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>78</b>	57	57
Manganese	ppm	ASTM D5185m	0	<b>1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>1215</b>	921	938
Calcium	ppm	ASTM D5185m	1070	<b>1344</b>	1018	1030
Phosphorus	ppm	ASTM D5185m	1150	<b>1203</b>	1029	1035
Zinc	ppm	ASTM D5185m	1270	<b>1532</b>	1213	1257
Sulfur	ppm	ASTM D5185m	2060	<b>3710</b>	3442	3485
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.4</b>	12.6	15.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.4</b>	9.2	▲ 0.0
Visc @ 100°C	cSt	ASTM D445	15.4	<b>15.2</b>	14.8	15.8



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0118243  
**Lab Number** : 06191832  
**Unique Number** : 11048584  
**Test Package** : FLEET

**Received** : 28 May 2024  
**Tested** : 29 May 2024  
**Diagnosed** : 30 May 2024 - Sean Felton

**GFL Environmental - 822 - Springfield Hauling**  
 2120 West Bennett Street  
 Springfield, MO  
 US 65807

Contact: Dennis Moore  
 dennis.moore@gflenv.com  
 T: (417)403-3641

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: