



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**4683M**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0117579</b>	GFL0108885	GFL0105587
Sample Date		Client Info		<b>23 May 2024</b>	19 Mar 2024	11 Dec 2023
Machine Age	hrs	Client Info		<b>16509</b>	15987	15184
Oil Age	hrs	Client Info		<b>14734</b>	14734	14734
Filter Age	hrs	Client Info		<b>14734</b>	9820	14734
Oil Changed		Client Info		<b>Changed</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>Changed</b>	Not Changd	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	<b>8</b>	6	6
Chromium	ppm	ASTM D5185m	>5	<b>1</b>	0	<1
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	2
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>1</b>	0	0
Aluminum	ppm	ASTM D5185m	>30	<b>2</b>	<1	<1
Lead	ppm	ASTM D5185m	>30	<b>&lt;1</b>	0	0
Copper	ppm	ASTM D5185m	>150	<b>1</b>	0	<1
Tin	ppm	ASTM D5185m	>5	<b>&lt;1</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>20	<b>4</b>	2	3
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	0	<1
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.3</b>	0.3	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.6</b>	6.0	6.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>17.9</b>	18.3	18.8
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>16</b>	2	1
Boron	ppm	ASTM D5185m	0	<b>4</b>	0	<1
Barium	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>60</b>	56	52
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	<1
Magnesium	ppm	ASTM D5185m	1010	<b>925</b>	982	996
Calcium	ppm	ASTM D5185m	1070	<b>1069</b>	1082	1095
Phosphorus	ppm	ASTM D5185m	1150	<b>1043</b>	1067	1051
Zinc	ppm	ASTM D5185m	1270	<b>1213</b>	1289	1236
Sulfur	ppm	ASTM D5185m	2060	<b>3278</b>	3741	3068
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.4</b>	14.2	14.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>9.5</b>	8.8	8.3
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.1</b>	14.0	13.9


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0117579 **Received** : 28 May 2024  
**Lab Number** : 06191947 **Tested** : 29 May 2024  
**Unique Number** : 11048699 **Diagnosed** : 29 May 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 415 - Michigan East**  
 6200 Elmridge  
 Sterling Heights, MI  
 US 48313  
 Contact: Frank Wolak  
 fwolak@gflenv.com  
 T: (586)825-9514  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)