



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR A344C 055585-1007
Component
Diesel Engine
Fluid
DIESEL ENGINE OIL SAE 10W30 (8 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0264441	LHMC73555	LHMC63547
Sample Date		Client Info		16 May 2024	29 Nov 2018	07 May 2013
Machine Age	hrs	Client Info		14242	10955	2186
Oil Age	hrs	Client Info		0	0	100
Filter Age	hrs	Client Info		0	0	100
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	5	15	8
Chromium	ppm	ASTM D5185m	>5	0	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	<1	<1
Titanium	ppm	ASTM D5185m		<1	6	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>15	1	2	1
Lead	ppm	ASTM D5185m	>30	<1	2	<1
Copper	ppm	ASTM D5185m	>125	0	2	<1
Tin	ppm	ASTM D5185m	>5	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>60	9	17	4
Potassium	ppm	ASTM D5185m	>20	2	2	3
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.7	2.3	0.5
Nitration	Abs/cm	*ASTM D7624	>20	5.7	8.7	5.
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.7	22.8	15.
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	4	4
Boron	ppm	ASTM D5185m	250	71	24	<1
Barium	ppm	ASTM D5185m	10	0	0	0
Molybdenum	ppm	ASTM D5185m	100	42	7	42
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	450	524	390	909
Calcium	ppm	ASTM D5185m	3000	1696	1816	1227
Phosphorus	ppm	ASTM D5185m	1150	788	998	1112
Zinc	ppm	ASTM D5185m	1350	905	1119	1302
Sulfur	ppm	ASTM D5185m	4250	2874	3664	3615
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.1	13.7	9.
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	9.8	---	---
Visc @ 100°C	cSt	ASTM D445	10.9	11.4	15.18	15.13


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : LH0264441
 Lab Number : 06193383
 Unique Number : 11050135
 Test Package : CONST (Additional Tests: TBN)

Received : 28 May 2024
 Tested : 30 May 2024
 Diagnosed : 30 May 2024 - Wes Davis

BEHR IRON
 2815 LIBERTY AVE.
 CLINTON, IA
 US 53732

Contact: SERVICE MANAGER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: