



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION



Machine Id
VOLVO EC380 314346

Component
Diesel Engine

Fluid
VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP449696	VCP436223	VCP396708
Sample Date		Client Info		18 May 2024	31 Oct 2023	14 Jun 2023
Machine Age	hrs	Client Info		3416	2009	2770
Oil Age	hrs	Client Info		0	0	500
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	Changed
Filter Changed		Client Info		N/A	N/A	Changed
Sample Status				ATTENTION	ATTENTION	SEVERE

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	5	6	0
Chromium	ppm	ASTM D5185m	>10	0	<1	0
Nickel	ppm	ASTM D5185m	>10	<1	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	2	2	6
Lead	ppm	ASTM D5185m	>20	<1	<1	<1
Copper	ppm	ASTM D5185m	>15	<1	1	1
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	5	5	2
Potassium	ppm	ASTM D5185m	>20	2	2	1
Fuel		WC Method	>6.0	<1.0	1.5	▲ 11.2
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	8.2	8.4	8.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.4	21.7	20.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

Sodium	ppm	ASTM D5185m		3	2	2
Boron	ppm	ASTM D5185m	2.5	32	23	20
Barium	ppm	ASTM D5185m	0.0	0	<1	12
Molybdenum	ppm	ASTM D5185m	0.7	43	47	51
Manganese	ppm	ASTM D5185m	0.0	<1	<1	0
Magnesium	ppm	ASTM D5185m	256	482	517	540
Calcium	ppm	ASTM D5185m	2057	1747	1658	1809
Phosphorus	ppm	ASTM D5185m	935	981	964	1001
Zinc	ppm	ASTM D5185m	1223	1132	1173	1186
Sulfur	ppm	ASTM D5185m	4079	3386	3601	3439
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.7	20.7	19.4
Base Number (BN)	mg KOH/g	ASTM D2896	10	9.2	9.0	8.6
Visc @ 100°C	cSt	ASTM D445	15.0	● 11.8	● 11.6	▲ 9.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP449696 **Received** : 29 May 2024
Lab Number : 06193694 **Tested** : 30 May 2024
Unique Number : 11050446 **Diagnosed** : 30 May 2024 - Sean Felton
Test Package : MOB 1 (Additional Tests: TBN)

ALTA EQUIPMENT/FLAGLER CONSTRUCTION EQUIPMENT LLC
 8418 PALM RIVER ROAD
 TAMPA, FL
 US 33619
 Contact: KENNY HANEY
 khaney@flaglerce.com
 T: (813)630-0077
 F: (813)630-2233

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)