



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 624K 1DW624KZEEE657948
Component
Diesel Engine
Fluid
SHELL ROTELLA T 15W40 (5 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0201419	JR0201413	JR0201420
Sample Date		Client Info		14 May 2024	22 Apr 2024	31 Mar 2024
Machine Age	hrs	Client Info		14325	14115	13911
Oil Age	hrs	Client Info		210	204	209
Filter Age	hrs	Client Info		210	204	209
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	8	7	6
Chromium	ppm	ASTM D5185m	>11	0	<1	0
Nickel	ppm	ASTM D5185m	>5	0	<1	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	3	2	1
Lead	ppm	ASTM D5185m	>26	0	<1	0
Copper	ppm	ASTM D5185m	>26	0	<1	0
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>22	5	6	4
Potassium	ppm	ASTM D5185m	>20	12	8	5
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	0.3	0.3
Nitration	Abs/cm	*ASTM D7624	>20	7.6	7.5	7.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.1	19.4	19.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	3	2	3
Boron	ppm	ASTM D5185m	316	134	151	125
Barium	ppm	ASTM D5185m	0.0	0	<1	0
Molybdenum	ppm	ASTM D5185m	1.2	10	12	13
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m	24	135	131	161
Calcium	ppm	ASTM D5185m	2292	2076	2115	2026
Phosphorus	ppm	ASTM D5185m	1064	1033	1114	1050
Zinc	ppm	ASTM D5185m	1160	1212	1223	1207
Sulfur	ppm	ASTM D5185m	4996	3834	3830	3821
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.4	15.5	16.2
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	8.0	8.8	8.2
Visc @ 100°C	cSt	ASTM D445	15.7	14.3	14.5	14.4


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : JR0201419

Lab Number : 06196376

Unique Number : 11058499

Test Package : CONST (Additional Tests: TBN)

Received : 31 May 2024

Tested : 03 Jun 2024

Diagnosed : 03 Jun 2024 - Wes Davis

Baxter Healthcare - Wood Boiler Biomass

2859 OLD LINVILLE RD

MARION, NC

US 28752

Contact: RICKY STYLES

ricky_styles@baxter.com

T: (828)756-4946

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)