



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

[47004]

Machine Id

HAMM H12I H2840096

Component

Diesel Engine

Fluid

JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (10 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0217619	JR0153287	JR0137214
Sample Date		Client Info		30 May 2024	21 Mar 2023	26 Jul 2022
Machine Age	hrs	Client Info		1629	945	498
Oil Age	hrs	Client Info		684	0	498
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	40	30	28
Chromium	ppm	ASTM D5185m	>20	1	2	2
Nickel	ppm	ASTM D5185m	>4	0	<1	<1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>20	7	5	4
Lead	ppm	ASTM D5185m	>40	5	<1	3
Copper	ppm	ASTM D5185m	>330	3	5	16
Tin	ppm	ASTM D5185m	>15	<1	<1	1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	22	21	27
Potassium	ppm	ASTM D5185m	>20	6	3	<1
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.6	0.5	0.3
Nitration	Abs/cm	*ASTM D7624	>20	9.0	9.6	10.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.9	22.6	21.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		13	3	4
Boron	ppm	ASTM D5185m		177	211	54
Barium	ppm	ASTM D5185m		<1	4	4
Molybdenum	ppm	ASTM D5185m		212	245	94
Manganese	ppm	ASTM D5185m		1	1	2
Magnesium	ppm	ASTM D5185m		739	746	153
Calcium	ppm	ASTM D5185m		1510	1624	2124
Phosphorus	ppm	ASTM D5185m		983	947	897
Zinc	ppm	ASTM D5185m		1161	1131	1126
Sulfur	ppm	ASTM D5185m		3481	3182	4372
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.7	16.9	16.8
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	8.2	9.0	6.9
Visc @ 100°C	cSt	ASTM D445	15.4	13.4	13.0	12.6


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Viscosity @ 100°C




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0217619 **Received** : 31 May 2024
Lab Number : 06196379 **Tested** : 03 Jun 2024
Unique Number : 11058502 **Diagnosed** : 03 Jun 2024 - Wes Davis
Test Package : CONST (Additional Tests: TBN)

B & S SITE DEVLOPMENT
 7800 PINEY BRANCH LANE
 BRISTOW, VA
 US 20136
 Contact: DANNY HUFF
 dhuff@bandssite.com
 T: (540)270-3203
 F: (703)753-0605

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)